AA 611-05 VAR Young, Erik 0297

MSA-5-1892-4706

12/6/25/2018 Comments 10/11/05/2018 12/11/07 NOW



STATE OF MARYLAND CRITICAL AREA COMMISSION CHESAPEAKE AND ATLANTIC COASTAL BAYS

1804 West Street, Suite 100, Annapolis, Maryland 21401 (410) 260-3460 Fax: (410) 974-5338 www.dnr.state.md.us/criticalarea/

February 7, 2007

Ms. Suzy Schappert Anne Arundel County Office of Planning and Zoning 2664 Riva Road, MS 6301 Annapolis, Maryland 21401

Re:

Young, Erik – 2006-0453-V,

previously approved as 2005-0388-V

Dear Ms. Schappert:

This office has received a variance request for the above referenced project. The applicant has requested a variance to allow an extension in time required for the implementation and completion of a previously approved variance, which was a variance to allow a dwelling with attached garage with less expanded Buffer than required. The property is designated a Limited Development Area (LDA) and is currently developed with a single-family dwelling and detached garage.

This office does not oppose the requested variance, provided the applicant follows the previously approved plan and conditions on the granted variance. The original plan provides that the applicant will construct the deck in a way that it remains pervious, which is done by leaving spaces between the boards, surfacing the area under the deck with gravel, and planting vegetation at the borders of the deck footprint. Conditions on which the Administrative Hearing Officer granted the previously approved variance include the following:

- 1) No further expansion of the proposed dwelling.
- 2) Mitigation for all disturbances to the Buffer, including those from forest clearing, grading, and construction footprint at a rate of 3:1. The mitigation will be done by planting native species on-site.

Thank you for the opportunity to provide comments. Please include this letter in your file and submit it as part of the record for this variance. Also, please notify the Commission in writing of the decision made in this case.

Ms. Suzy Schappert February 7, 2007 Page Two

Sincerely,

Amber Widmayer

Natural Resources Planner

cc:

AA 611-05

Robert L. Ehrlich, Jr.

Michael S. Steele



Martin G. Madden Chairman

Ren Serey
Executive Director

STATE OF MARYLAND CRITICAL AREA COMMISSION CHESAPEAKE AND ATLANTIC COASTAL BAYS

1804 West Street, Suite 100, Annapolis, Maryland 21401 (410) 260-3460 Fax: (410) 974-5338 www.dnr.state.md.us/criticalarea/

December 8, 2005

Ms. Liz West Anne Arundel County Office of Planning and Zoning 2664 Riva Road, MS 6301 Annapolis, Maryland 21401

Re:

Variance 2005-0297-V, revised

Erik Young

Dear Ms. West:

This office has received revised plans for the above referenced variance following a meeting with the applicant and his consultants on November 16, 2005. This letter supercedes our previous letters. The applicant is requesting a variance to build a dwelling with attached garage with less expanded Buffer than required. The property is designated a Limited Development Area (LDA) and is currently developed with a single-family dwelling and detached garage. We have the following comments.

- 1. The site is 4.32 acres and has 12,898 square feet of existing impervious surface (6.9%). The revised plans reduce impervious surface to 12,244 square feet (6.5%), a reduction of 654 square feet.
- 2. The existing dwelling is almost entirely within the expanded Buffer; the existing garage is outside the Buffer. The proposed dwelling is partially over the existing footprint in the Buffer and partially outside the Buffer. The proposed garage is entirely out of the Buffer. The revised plans pull the dwelling further out of the Buffer than it currently exists and as shown on the earlier proposal. It is our understanding that the existing foundation is failing and cannot be reused. Existing impervious surface in the expanded Buffer is 2963 square feet. Proposed impervious surface in the expanded Buffer is 1915 square feet.
- 3. 840 square feet of the existing driveway loop is proposed for removal.
- 4. The applicant will be installing a nitrogen removing septic system.

Ms. West December 8, 2005 Page Two

5. The proposed well is within the expanded Buffer. The existing well within the expanded Buffer will be abandoned.

Provided this property is properly grandfathered, we do not oppose this variance. We recommend mitigation, at a 3:1 ratio for disturbance within the Buffer, be required. Mitigation plantings should be accommodated on the site to the extent possible.

Thank you for the opportunity to provide comments. Please include this letter in your file and submit it as part of the record for this variance. Also, please notify the Commission in writing of the decision made in this case.

Sincorely, Lamal Colinger

Regina A. Esslinger, Chief Project Evaluation Division

RAE/jjd

cc: AA611-05

Robert L. Ehrlich, Jr.

Michael S. Steele Lt. Governor



Martin G. Madden Chairman

Ren Serey
Executive Director

STATE OF MARYLAND CRITICAL AREA COMMISSION CHESAPEAKE AND ATLANTIC COASTAL BAYS

1804 West Street, Suite 100, Annapolis, Maryland 21401 (410) 260-3460 Fax: (410) 974-5338 www.dnr.state.md.us/criticalarea/

October 11, 2005

Ms. Liz West Anne Arundel County Office of Planning and Zoning 2664 Riva Road, MS 6301 Annapolis, Maryland 21401

Re:

Variance 2005-0297-V

Erik Young

Dear Ms. West:

This letter supplements my letter dated October 6, 2005. This office has received additional revised plans for the above referenced variance dated October 10, 2005. The most recent revision concerns the Buffer delineation; it shows the extent of the expanded Buffer as a line that bisects the proposed dwelling, with the proposed garage and driveway out of the expanded Buffer. The earlier Buffer delineation showed the entire existing dwelling and garage in the Buffer, with only a small oval area outside the Buffer.

The most recent information provided by the applicant indicates that the proposed impervious surface in the Buffer is 3537 square feet, not 2693 square feet as previously indicated. I have requested a breakdown of existing and proposed impervious surfaces in the Buffer to verify this figure. I may have additional comments once I receive this information.

Thank you for the opportunity to provide comments. Please include this letter in your file and submit it as part of the record for this variance. Please notify the Commission in writing of the decision made in this case.

Sincerely,

Regina A. Esslinger, Chief

Project Evaluation Division

cc: Ms. Scarlett Breeding, Alt Breeding Schwartz

AA611-05

Robert L. Ehrlich, Jr. Governor

Michael S. Steele



Martin G. Madden Chairman

Ren Serey
Executive Director

STATE OF MARYLAND CRITICAL AREA COMMISSION CHESAPEAKE AND ATLANTIC COASTAL BAYS

1804 West Street, Suite 100, Annapolis, Maryland 21401 (410) 260-3460 Fax: (410) 974-5338 www.dnr.state.md.us/criticalarea/

October 6, 2005

Ms. Liz West Anne Arundel County Office of Planning and Zoning 2664 Riva Road, MS 6301 Annapolis, Maryland 21401

Re:

Variance 2005-0297-V

Erik Young

Dear Ms. West:

This office has received revised plans for the above referenced variance following a meeting with the applicant and his consultants on October 4, 2005. This letter supercedes our September 28, 2005 letter. The applicant is requesting a variance to build a dwelling with attached garage with less expanded Buffer than required. The property is designated a Limited Development Area (LDA) and is currently developed with a single-family dwelling and detached garage. We have the following comments.

- 1. The site is 4.32 acres and has 14,080 square feet of existing impervious surface (7.48%). The revised plans reduce impervious surface to 13,042 square feet (6.9%), a reduction of 1038 square feet.
- 2. The existing dwelling and garage are entirely within the expanded Buffer. The proposed dwelling is partially over the existing footprint, and the proposed garage is almost entirely over the garage footprint. It is our understanding that the existing foundation is failing and cannot be reused. Existing impervious surface in the expanded Buffer is 2806 square feet. Proposed impervious surface in the expanded Buffer is 2693 square feet.
- 3. The applicant will be installing a nitrogen removing septic system.

Provided this property is properly grandfathered, we do not oppose this variance. We recommend mitigation, at a 3:1 ratio for disturbance within the Buffer, be required. Mitigation plantings should be accommodated on the site to the extent possible.

Ms. West October 6, 2005 Page Two

Thank you for the opportunity to provide comments. Please include this letter in your file and submit it as part of the record for this variance. Also, please notify the Commission in writing of the decision made in this case.

Sincerely,

Regina A. Esslinger, Chief Project Evaluation Division

RAE/jjd

cc: Ms. Scarlett Breeding, Alt Breeding Schwartz

AA611-05

Robert L. Ehrlich, Jr. Governor

Michael S. Steele



Martin G. Madden Chairman

Ren Serey
Executive Director

STATE OF MARYLAND CRITICAL AREA COMMISSION CHESAPEAKE AND ATLANTIC COASTAL BAYS

1804 West Street, Suite 100, Annapolis, Maryland 21401 (410) 260-3460 Fax: (410) 974-5338 www.dnr.state.md.us/criticalarea/

September 28, 2005

Ms. Lori Rhodes Anne Arundel County Office of Planning and Zoning 2664 Riva Road Annapolis, MD 21401

RE: Variance 2005-0297-V Erik Young

Dear Ms. Rhodes:

Thank you for providing information on the above referenced variance. The applicant is requesting a variance to permit the removal and replacement of the existing single-family dwelling with a new dwelling, attached garage, porches, covered storage, walkways, well, and septic systems within the expanded Buffer. The property is designated a Limited Development Area (LDA) and is currently developed with a single-family dwelling, deck, walkways, detached garage, concrete pad, retaining wall, gravel driveway, pier, septic, well, and an underground home fuel storage tank.

Providing that this property grandfathered, this office does not oppose a variance to rebuild a dwelling; however, impacts must be minimized and the variance the minimum necessary. At this time, we do not believe the variance requested is the minimum necessary. Based on the information provided, we have the following comments regarding the development proposal and variance request.

As stated in the Critical Area Report, steep slopes and the expanded Buffer encumbers almost the entire property. The proposed dwelling lies partially within the footprint of the existing dwelling. The proposed dwelling is within 10 feet of the top of steep slopes. The expanded Buffer must be correctly noted on the plans.

Lori Rhodes Variance 2005-0297-V Erik Young September 28, 2005 Page 2

- The lot is 188,307 square feet and the applicant proposes 22,322 square feet of disturbance and 15,994 square feet impervious surface coverage for the new dwelling, porches, walkways, and attached garage/covered storage area, and driveway. The proposed septic system and two dry wells are located on the east side of the proposed dwelling. The proposed dwelling footprint is 2,954 square feet and the proposed garage is 1,021 square feet for a total of 3,975 square feet. The existing dwelling footprint is approximately 2,162 square feet and the existing garage footprint is approximately 400 square feet for a combined impervious surface coverage of 2,562 square feet.
- 3) Minimization of impacts could include items such as: removing the covered storage behind the proposed garage, reducing the proposed garage, and reducing or eliminating the covered porch on the southwest side of the proposed dwelling. Also, the connection between the main dwelling and garage could be reduced in size or eliminated. The proposed dwelling could be expanded by adding a second story to the existing dwelling while not expanding impervious surface. There is ample room on this property to accommodate both the property owner's intent to improve the dwelling while at the same time reducing impacts to the expanded Buffer.

Thank you for the opportunity to provide comments. Please include this letter in your file and submit it as part of the record for this variance. Also, please notify the Commission in writing of the decision made in this case.

Sincerely,

Gary Green

Environmental Analyst

cc:

AA621-05

IN THE OFFICE OF ADMINISTRATIVE HEARINGS

CASE NUMBER 2006-0451-V

IN RE: ERIK YOUNG

SECOND ASSESSMENT DISTRICT

DATE HEARD: FEBRUARY 20, 2007

ORDERED BY: STEPHEN M. LeGENDRE, ADMINISTRATIVE HEARING OFFICER

PLANNER: JOHN FURY

FEB 2 3 2007

CRITICAL AREA COMMISSION
Chesapeake & Atlantic Coastal Bays

DATE FILED: FEBRUARY 2, 2007

PLEADINGS

Erik Young, the applicant, seeks a variance (2006-0451-V) to extend the time for implementation and completion of a previously approved variance on property located along the east side of Childs Point Road, east of Forest Drive, Annapolis.

PUBLIC NOTIFICATION

The hearing notice was posted on the County's web site in accordance with the County Code. The file contains the certification of mailing to community associations and interested persons. Each person designated in the application as owning land that is located within 175 feet of the property was notified by mail, sent to the address furnished with the application. Terry Schuman, the applicant's engineering consultant, testified that the property was posted for more than 14 days prior to the hearing. I find and conclude that the requirements of public notice have been satisfied.

FINDINGS AND CONCLUSIONS

This case concerns the same property the subject of a decision by this office in Case No. 2005-0297-V (December 21, 2005). The prior Order conditionally approved variances to disturbed the Chesapeake Bay Critical Area buffer as expanded by steep slopes and the edge of the slopes for the construction of a dwelling. At the time of the approval, Anne Arundel County Code, Article 18,

Section 18-16-405(a) provided that a variance expires by operation of law unless the applicant obtains a building permit within one year. Thereafter, the variance shall not expire so long as construction proceeds in accordance with the permit. The present request is a timely application for an extension.

John Fury, a planner with the Office of Planning and Zoning, testified that the grading permit issued but the building permit has been delayed by the need to record a subdivision plat. There were no adverse agency comments. By way of conclusion, Mr. Fury supported the application.

Terry Shuman, the applicants' engineering consultant, testified that the subdivision plat legalizes the lot, which was improperly subdivided in the 1960's. The applicant requests an additional year to obtain the permit. The conditions of the prior variance are unchanged. There was no other testimony in the matter.

Upon review of the facts and circumstances, I find and conclude that the applicant is entitled to relief from the code. In this regard, I adopt the findings and conclusions of the prior Order. There is no indication of any change in the outcome and the applicant has justified the need for additional time. The approval incorporates the same conditions of the prior Order.

ORDER

PURSUANT to the application of Erik Young, petitioning for a variance to extend the time for the implementation and completion of a previously approved variance; and

PURSUANT to the notice, posting of the property, and public hearing and in accordance with the provisions of law, it is this 21 day of February, 2007,

ORDERED, by the Administrative Hearing Officer of Anne Arundel County, that the applicant is **granted** variances to extend the time for the building permit until February 21, 2008 with completion in accordance with the permit.

The foregoing approval is subject to the following conditions:

- 1. No further expansion of the dwelling is allowed and no additional impervious surfaces are allowed.
- 2. The building permit is subject to the approval of the Department of Health.
- 3. The applicant shall provide mitigation at a 3:1 ratio with plantings of native species onsite.

Stephen M. LeGendre

Administrative Hearing Officer

NOTICE TO APPLICANT

Within thirty days from the date of this Decision, any person, firm, corporation, or governmental agency having an interest therein and aggrieved thereby may file a Notice of Appeal with the County Board of Appeals.

If this case is not appealed, exhibits must be claimed within 60 days of the date of this Order, otherwise that will be discarded.

IN THE OFFICE OF ADMINISTRATIVE HEARINGS

CASE NUMBERS 2005-0297-V

IN RE: ERIK YOUNG

SECOND ASSESSMENT DISTRICT

DATE HEARD: DECEMBER 13, 2005

ORDERED BY: STEPHEN M. LeGENDRE, ADMINISTRATIVE HEARING OFFICER

PLANNER: LIZ WEST

DATE FILED: DECEMBER 2/, 2005



PLEADINGS

Erik Young, the applicant, seeks a variance (2005-0297-V) to permit a dwelling and associated facilities with less buffer than required and with disturbance to steep slopes on property located along the east side of Childs Point Road, east of Forest Drive, Annapolis.

PUBLIC NOTIFICATION

The hearing notice was posted on the County's web site in accordance with the County Code. The file contains the certification of mailing to community associations and interested persons. Each person designated in the application as owning land that is located within 175 feet of the property was notified by mail, sent to the address furnished with the application. Terry Schuman, the applicant's engineering consultant, testified that the property was posted on September 28, 2005. I find and conclude that the requirements of public notice have been satisfied.

FINDINGS AND CONCLUSIONS

The applicant owns a single-family residence with a street address of 870 Childs Point Road, in the Bywater Estates subdivision, Annapolis. The property comprises 4.3 acres and is zoned R-1 Residential with a Chesapeake Bay Critical Area designation as Limited Development Area (LDA). This is a waterfront lot on Church Creek. The request is to raze the existing dwelling and a detached garage,

followed by redevelopment of the property with a new dwelling and attached garage. The project disturbs the Chesapeake Bay Critical Area buffer as expanded by steep slopes and the edge of steep slopes.

Anne Arundel County Code, Article 18, Section 18-13-104 creates a 100foot buffer from tidal waters. The buffer expands to include all lands within 50
feet of contiguous steep slopes. Article 17, Section 17-8-201 proscribes
disturbance on slopes greater than 15 percent in the LDA. Accordingly, the
proposal requires a variance to the expanded buffer and a variance to disturb steep
slopes.

Liz West, a planner with the Office of Planning and Zoning, testified that the property is below the minimum width for the R-1 district and occupies a point of land in Church Creek. The existing dwelling was built in the 1940s at a distance of 130 feet from water. The new dwelling is 137 feet from water. The replacement septic system in the rear yard precludes relocating the new dwelling further from water. There is a net reduction in imperious surfaces in the expanded buffer (from 2,963 square feet to 1,915 square feet). The slope disturbance, which is associated with the new well, is very minor. The project meets the allowances for clearing and impervious surfaces. The witness summarized the agency comments. The Chesapeake Bay Critical Area Commission requested mitigation at a 3:1 ratio. The Department of Health requested plan approval. The

¹ The footprint of the existing dwelling is 1997 square feet, including the porch (101 square feet) and atgrade deck (255 square feet); the footprint of the detached garage is 618 square feet. The footprint of the new dwelling is 3,777 square feet, including the porch (215 square feet) and attached garage (734 square feet). (The calculation for the new dwelling does not include a pervious deck addition.)

Development Review Division questioned the extent of the relief because the design incorporates a breezeway connection to the garage. By way of conclusion, Ms. West supported the application.

Dr. Young summarized a written statement in support of the application. In brief, the structurally unsound existing home is situated on a knoll that slopes away in all directions. Rebuilding on the same foundation would cause greater slope disturbance than the construction of the new home. There is a 5% net reduction of impervious surfaces for the entire property. The design incorporates first floor living because the applicant and his wife are both suffering from degenerative medical conditions. Finally, in response to the negative comment from the Development Review Division, the breezeway connection is not in the expanded buffer.

Mr. Schuman summarized the site constraints and submitted a series of color coded exhibits (existing impervious, proposed impervious, existing impervious to be removed, and reduction of impervious in buffer) as well as site tabulations for the existing and proposed conditions. Areas in the expanded buffer where impervious surfaces are removed would be available for mitigation.

Scarlett Breeding, the applicant's architect, confirmed that the existing foundation is beyond reuse and rebuilding in the same location would cause greater disturbance to the expanded buffer and steep slopes than the new dwelling. She also supplied a list of waterfront properties with development that is considered comparable to the applicant's request.

Eric See, an environmental consultant to the applicant, submitted a Critical Area Report and opined that the variance standards are satisfied.

Upon review of the facts and circumstances, I find and conclude that the applicant is entitled to relief from the code. For this Critical Area property, due to the extent of the expanded buffer and steep slopes, a strict implementation of the program would result in an unwarranted hardship. To literally interpret the program would deny the applicant the right to redevelop the property with a single-family dwelling, a right commonly enjoyed by other properties in similar areas of the Critical Area. Conversely, the granting of the variance will not confer any special privilege that the program typically denies. There is no indication that the request results from the actions of the applicant or from land use on neighboring property. Finally, with mitigation and other conditions, the granting of the variance will not adversely impact Critical Area resources and will harmonize with the general spirit and intent of the program.

I further find that the variances represent the minimum relief. The primary request is to disturb the expanded buffer. Despite the very substantial replacement home, there is a fairly significant reduction in impervious surfaces in the expanded buffer. The new dwelling is nominally further from water and there is a modest (654 square feet) reduction in impervious coverage for the entire property. There was nothing to suggest that the granting of the variances would alter the essential character of the neighborhood, substantially impair the appropriate use or

development of adjacent property or cause a detriment to the public welfare. The approval is subject to the conditions in the Order.

ORDER

PURSUANT to the application of Erik Young, petitioning for a variance to permit a dwelling and associated facilities with less buffer than required and with disturbance to steep slopes; and

PURSUANT to the notice, posting of the property, and public hearing and in accordance with the provisions of law, it is this 21st day of December, 2005,

ORDERED, by the Administrative Hearing Officer of Anne Arundel County, that the applicant is **granted** variances to disturb the expanded buffer and steep slopes to permit a dwelling and associated facilities in accordance with the site plan.

The foregoing variances are subject to the following conditions:

- 1. No further expansion of the dwelling is allowed and no additional impervious surfaces are allowed.
- 2. The building permit is subject to the approval of the Department of Health.
- 3. The applicant shall provide mitigation at a 3:1 ratio with plantings of native species onsite.

Stephen M. LeGendre

Administrative Hearing Officer

NOTICE TO APPLICANT

Within thirty days from the date of this Decision, any person, firm, corporation, or governmental agency having an interest therein and aggrieved thereby may file a Notice of Appeal with the County Board of Appeals.

Further Section 18-16-405(a) provides that a variance expires by operation of law unless the applicant obtains a building permit within one year. Thereafter, the variance shall not expire so long as construction proceeds in accordance with the permit.

If this case is not appealed, exhibits must be claimed within 60 days of the date of this Order, otherwise that will be discarded.

AA 0611-05

Blumenthal, Delavan & Williams, P.A.

HARRY C. BLUMENTHAL* CHARLES F. DELAVAN SAGER A. WILLIAMS, JR.**

* ADMITTED IN MD & DC

** AMERICAN INSTITUTE OF
CERTIFIED PLANNERS

ATTORNEYS AT LAW
SUITE 240
170 JENNIFER ROAD
ANNAPOLIS, MARYLAND 2140

ANNAPOLIS (410) 573-2900 BALTIMORE (410) 841-6444 WASHINGTON (301) 261-8555 TELECOPIER (410) 573-2907 www.bdwlawfirm.com

COUNSEL
EILEEN E. POWERS
BARBARA J. PALMER
JOHN GREGORY SMITH

November 22, 2005

Liz West, Zoning Analyst Anne Arundel County Office of Planning and Zoning 2664 Riva Road, 3rd Floor Annapolis, MD 21401

Dear Ms. West:

I sincerely appreciate the opportunity afforded to my client, Dr. Erik Young and his architectural and engineering consultants to discuss with you and Regina Esslinger the Critical Area variance application filed by Dr. and Mrs. Young. This application seeks approval to remove an existing house located at 870 Child's Point Road fronting on Church Creek in the Annapolis area of Anne Arundel County, and to construct in its place a new residence, which would be partially located in the expanded buffer established by Anne Arundel County's Critical Area regulations.

Dr. and Mrs. Young, their architect, Scarlett Breeding, and their civil engineer, Terry Schuman, have worked diligently to tailor the footprint and the design of the proposed residence to minimize the impact within the Critical Area by reducing the amount of the proposed structure in the expanded buffer area and by increasing the distance of the proposed structure from tidalwater as compared with the existing house.

The existing house was built in the 1940's, and with the passage of time, has become structurally unsound and would have to be substantially rebuilt in order to be habitable. Because the existing house is totally within the expanded buffer, the impacts of such a reconstruction project would have a significant adverse affect on nearby steep slopes and the integrity of the Critical Area.

In the planning of a replacement structure for the existing house, the applicants have had to accommodate the Applicants' physical impairments, which affect the type of structure which has been proposed. Mrs. Young is legally blind and it is important that the essential living area that she would use in this structure is laid out on one floor to preclude the necessity for climbing or descending steps as a part of her daily life. Dr. Young suffers from spinal deterioration which interferes with his ability to use stairs. Additionally, Dr. Young requires a

NOV 28 2005

Liz West November 22, 2005 Page 2 of 4

"breezeway area" between the proposed garage and the residence so as to avoid having to move from his vehicle to the house in exposed areas subject to snow and ice.

In addition to the physical limitations of the applicants, the location of the house has been dictated to some degree by the constraints of the site itself. Significant in this regard is the design of the proposed septic system containing a septic tank, septic transmission lines and a drywell, the locations of which are dictated by the locations of approved percolation tests within the site. The buildable envelope is further constrained by the location of steep slopes, which virtually surround the site, and the extent of the expanded Critical Area buffer. While the lot upon which this house would be located is approximately 4.5 acres in size, its shape is long and narrow, and the building area is severely constrained due to steep slopes, the expanded buffer and the location of significant trees which are to be preserved.

The original Critical Area variance site plan which was filed with your department contained some erroneous information which required recalculation and correction before the matter would be heard before the Administrative Hearing Officer. Mr. LeGendre graciously approved a postponement of the previously scheduled variance hearing in order to allow the site plan to be corrected. In the interim period Scarlett Breeding and Terry Schuman have worked diligently to refine the site plan to further minimize the disturbance to the expanded buffer, to preserve existing trees, and to minimize further the extent of impervious surface on the property.

The results of those efforts are reflected in a new variance site plan set for 870 Child's Point Road, "Lot 9, Bywater Estates". In addition to the revised variance site plan, Scarlett Breeding has prepared revised color-coded site plans showing the existing impervious coverage, the proposed impervious coverage, existing impervious [area] to be removed and the reduction of impervious [area] in the buffer. Ms. Breeding has also prepared a tabulation comparing the existing structure and the proposed structure with respect to changes in impervious coverage within the buffer, outside the buffer, and site-wide, the footprint of the existing structure compared to the proposed structure, and the area of disturbance within the expanded buffer and on the total site.

Liz West November 22, 2005 Page 3 of 4

These exhibits also provide great detail regarding the site features including steep slopes, existing significant trees and other site data and constraints which have lead to the design of the proposed structure.

These exhibits demonstrate the following:

- (1) The area of impervious coverage created by the proposed house within the expanded Critical Area buffer will be reduced by 1,048 square feet as compared to the existing house.
- (2) The impervious coverage on the total site will be reduced by 654 square feet (when comparing the existing structure and improvements with the proposed structure and improvements).
- (3) The total footprint of the proposed residential structure and its associated accessory components will be slightly increased from 3,912 square feet (total footprint) to 4,177 square feet (total footprint).
- (4) The distance between the proposed structure and the water has been increased by approximately 10 feet on all sides as compared with the existing structure.
- (5) Significant components of the residence, the breezeway and the garage have been relocated to areas outside of the expanded buffer.
- The site design has been revised to preserve existing mature trees, reuse existing driveway surfaces and to locate the septic areas on the site in areas which will cause the least impact to the Critical Area. Additionally, the applicant proposes a nitrogen removal system to be incorporated into the septic system to further minimize ground water impact or impact to the tidewater area.

I believe that the applicants have taken significant and laudable steps to improve the site plan which is being submitted with this letter and to minimize the

Blumenthal, Delavan & Williams, P.A.

Liz West November 22, 2005 Page 4 of 4

impacts of this project on the Critical Area, particularly as compared with the impact which would be occasioned by the renovation of the existing structure in its present location.

I hope that your department can conclude that the applicant has met its burden to minimize the extent of the variance requested and that you can conclude that your department can and should support this Critical Area variance request. Thank you for your cooperation in this effort.

Sincerely yours,

ned

Charles F. Delavan

CFD/jf

CC:

Dr. Young Scarlett Breeding Terry Schuman Regina Esslinger

OneMedicine Associates

Neil Spiegel D.O. Inc. 6211 Executive Boulevard Rockville, MD. 20852 (301) – 231-5600 MAN SS SOLD

November 17, 2005

Steve Legendre, Esq. Administrative Hearing Officer 44 Calvert Street Annapolis MD 21401

Dear Sir,

I have treated Doctor Young for the past 6 years for chronic neuropathic pain that has resulted from hemiated and degenerative discs in his cervical spine. MRI findings include: multilevel degenerative disc disease/cervical spondylosis and arthritis, compression of the C5 and C6 nerve roots, and compression of the spinal cord. In addition he also has EMG evidence of bilateral compression neuropathies of the radial and median nerves. The spinal cord compression has resulted in early myelopathic changes, which results in impaired function of his lower extremities and bladder.

Dr. Young experiences problems with tactile sensation, fine motor control, and diminished proprioception in all four extremities. He has difficulty walking at times as well as problems negotiating stairs and walking on ice and snow. At times he will report bladder irritability associated with urinary urgency. It is my opinion that when designing a residence, the master suite should be on the first floor and the garage should be attached to the house. This will reduce his risk of falling and help reduce cold induced bladder spasms when he leaves his house during the winter months.

Sincerely yours.

Neil Spiegel, D.O. Physical and Renabilitative Medicine 9707 Medical Center Drive Suite 110 Rockville, MD 20850 (301) 424-7744

October 5, 2005

Steve Legendre, Esq.
Administrative Hearing Office
44 Calvert Street
Annapolis, MD 21401

Re: Joyce Young's Visual Disability

Dear Mr. Legendre:

I have cared for Mrs. Joyce Young since 1988. In addition to the care I provided her, she receives care from a retinal specialist at the Wilmer Eye Clinic at Johns Hopkins University. Mrs. Young suffers from retinitis pigmentosa. This condition is a progressive, degenerative disease of the retina which is characterized by a gradual loss of peripheral vision and the ability to see in darkness. It is an inherited disorder and in the case of Mrs. Young, her father, several of her siblings, and several of her nieces and nephews are affected. In addition, presence of the disease has not been ruled out in all of her children. Mrs. Young has been symptomatic with this disease since her early twenty's and her symptoms have progressed to the point that at this time she can no longer drive, she has a significant loss of her peripheral vision, and she has night blindness. Given the fact that her father is totally blind and other family members are severely affected by this disease, it is likely that Mrs. Young will be become totally blind in the future.

With this in mind, it is very appropriate that in the course of designing a new residence, she and her husband wish to placed the master suite on the first floor and orient the house toward the South and Southwest so that the common living areas will be well lit with natural sunlight.

Sincerely yours,

Edward Tsoy, M.D.

Fellow, American Academy of Ophthalmology



Page & A CORPA & DOWN LINE IN a specimon capación a concessor a c Programme and the control of the

DAVID WALLACE: P.E. Structural Consultation

November 17, 2005

Dr. Erik B. Young, MD Medical Center Development Corp. 15005 Shady Grove Road Suite 350 Rockville, MD 20850

Re: 870 Childs Point Road


Dear Dr. Young:

Thank you for the opportunity to consult with you regarding your house in Annapolis. As you are aware, we met at the site on November 10^{th} to inspect the structure.

Visual inspection revealed a long horizontal crack and an inward bulge in the north wall, and some step cracking at the southeast corner. The cracks constitute a structural failure that will require remediation. Additionally, the 8" block used in the foundation of this older house is not up to today's code, which requires 12" block.

I would therefore recommend a structural repair of the bulged north wall section and retrofitting of the foundation with vertical #4 reinforcing bars approximately 4 feet on center around the entire perimeter.

Please call if you have any questions.





June 6, 2005

Department of Planning and Zoning 2664 Riva Road, Third Floor Annapolis, MD 21401 Attention: Ms. Suzanne Schappert

RE:

Erik B. Young and Joyce Young LOT 9 "BYWATER ESTATES" TAX MAP 51, GRID 21, PARCEL 169 TAX ACCT. #02-145-01867400 VARIANCE REQUEST LETTER OF EXPLANATION

Dear Zoning:

The purpose of this letter is to outline the applicant's request for relief from Article 27, Title 13, Section 104(a) Critical Area Overlay Zone - expanded buffer setback. The applicant is seeking relief to the required 50- foot setbacks to the top of steep slopes in order to re-develop the house and accessory structure. Because of unique physical constraints such as lot shape and topographic features predominately steep slopes and associated buffers there, is no reasonable possibility of re-developing this property in strict conformance within zoning regulations. Granting of this variance is necessary to avoid practical difficulties.

The property is located on the east side of Childs Point Road, House number 870 (formerly Bywater Road), approximately 5,700 feet south of Forest Drive Annapolis, Maryland 21401, and consists of 4.3 Acres. The site is waterfront and designated as LDA Chesapeake Bay Critical Area. The property is zoned R1. The property is currently developed with a single family detached dwelling and accessory structures. Water and Sewer services are private.

The applicant is seeking to replace the existing structure as it is outdated and has structural concerns with respect to the foundation. The applicant has obtained current approval from the Health Department for a new septic system under application T02033599. The water source will remain the same.

The lot was created by plat in July 1946 and the structure was constructed in 1948 (approximately). The property is irregular in shape; 845 feet deep, 109' feet wide at the street and widens towards the waters edge. The enclosed plan reflects field run boundary and topographical data which show that the site is severely constrained by steep slopes and expanded buffer. We have discussed this site with the Office of Planning and Zoning with respect to the determination of buffers and proposed development within the expanded buffer.

The existing dwelling is located 10 feet from the top of the steep slopes; therefore the applicant seeks a variance of 40 feet to the 50' expanded buffer for the purpose of expanding and reconfiguring the existing development. The applicant does not propose disturbance to the steep slopes. The applicant has specified 3:1 mitigation for removal of woodland within the disturbed area.

Should you have any questions, comments, or require any additional information, please do not hesitate to contact me directly at 410-897-9290.

Sincerely,

Bay Engineering, Inc.

Gary M. Evans

Senior Project Manager

Cc. Mr. Erik Young, Owner

Mrs. Scarlett Breeding, Architect

File



CHESAPEAKE BAY CRITICAL AREA REPORT

Variance Application for:

Erik B. Young

For Lot at:

870 Childs Point Road, Lot 9, Bywater Estates Subdivision Annapolis, Maryland 21403

Tax Map 51, Grid 21, Parcel 169, Lot 9

Critical Area Designation: RCA

Zoning: R-1

January, 2004

I. Introduction

The applicant is proposing to add additions and modify an existing waterfront home on this 4.3-acre parcel in the Bywater Estates Subdivision outside Annapolis, Anne Arundel County. The property is completely within the Chesapeake Bay Critical Area, with a Resource Conservation (RCA) land use designation. (See the enclosed copy of County Map # 24.)

The site is constrained by the expansion of the 100-foot Buffer due to steep slopes, placing most of the footprint of the existing house, garage, and driveway within the Expanded Buffer. Adding additions to the house and regrading the area around it would therefore disturb the Expanded Buffer. Therefore, a variance to Article 28, □1A-105(a)(1) is required.

This report is based on 2004 site plan by Bay Engineering, Inc. a copy of which is enclosed in the pocket at the end of this report.

II. Critical Area Study Narrative - Site Description

The subject waterfront property is is a 4.3 acre parcel located on Childs Point Road (formerly, Bywater Road) south of Annapolis. It is characterized by a ridge that extends between two ravines to a bluff overlooking Church Creek. An existing house with detached garage is located at the end of the ridge on the bluff, and an existing paved driveway runs from the street along the ridge to the house.

The adjoining lots on either side are currently developed with houses of similar locations and sizes. The house portion of the site is mapped in the 1973 Soil Survey for Anne Arundel County, Maryland with the well-drained Monmouth fine sandy loam, 15-40% slopes (MvE) mapping unit. However, the ridge top is much less steep and all proposed improvements are located on slopes less than 15%.

A site investigation was conducted on May 23, 2005, by Eric E. See of See Environmental Services, Inc. No plant species were observed that are considered rare, threatened or endangered by the U.S. Fish & Wildlife Service or the Maryland Department of Natural Resources (DNR).

III. Proposed Conditions/Critical Area Compliance

There is 0.39 acre of impervious coverage. Construction of the proposed house addition and changes to the driveway and garage would create a total of 0.375 acre, or 3.9% of the site, well under the 15% maximum allowed in LDA.

Tree cover (forest and developed woodlands: tress over mowed lawn and ornamental plantings) is approximately 3.5 acres. Proposed clearing of individual trees around the existing house would be approximately 3,000 square feet (based on estimated canopy area estimated by DBH of trees proposed to be removed). This would be well under the 20% allowed in RCA with 1-to-1 replacement required.

Stormwater management is proposed as additional plantings and rooftop disconnection. Sediment control measures will be developed at time of Grading Permit, and may include use of super silt/reinforced silt fence.

IV. Variance Standards:

Because the entire ridge top on which the existing house sites is in the Expanded Buffer, no exterior additions or improvements can occur without a variance.

With stormwater management and sediment controls during construction and with reforestation provided by on-site replacement, construction of the proposed house should be able to completed without significant impacts to water quality and fish and wildlife habitat.

References

Anne Arundel County PACE. Critical Area Map #24.

Bay Engineering, Inc., 2005 site plans and field surveys.

Soil Conservation Service, 1967. Soil Survey for Anne Arundel County, Maryland. USDA.





CHESAPEAKE BAY CRITICAL AREA REPORT

Variance Application for:

Erik B. Young

For Lot at:

870 Childs Point Road, Lot 9, Bywater Estates Subdivision Annapolis, Maryland 21403

Tax Map 51, Grid 21, Parcel 169, Lot 9

Critical Area Designation: RCA

Zoning: R-1

January, 2004

I. Introduction

The applicant is proposing to add additions and modify an existing waterfront home on this 4.3-acre parcel in the Bywater Estates Subdivision outside Annapolis, Anne Arundel County. The property is completely within the Chesapeake Bay Critical Area, with a Resource Conservation (RCA) land use designation. (See the enclosed copy of County Map # 24.)

The site is constrained by the expansion of the 100-foot Buffer due to steep slopes, placing most of the footprint of the existing house, garage, and driveway within the Expanded Buffer. Adding additions to the house and regrading the area around it would therefore disturb the Expanded Buffer. Therefore, a variance to Article 28, □1A-105(a)(1) is required.

This report is based on 2004 site plan by Bay Engineering, Inc. a copy of which is enclosed in the pocket at the end of this report.

II. Critical Area Study Narrative - Site Description

The subject waterfront property is is a 4.3 acre parcel located on Childs Point Road (formerly, Bywater Road) south of Annapolis. It is characterized by a ridge that extends between two ravines to a bluff overlooking Church Creek. An existing house with detached garage is located at the end of the ridge on the bluff, and an existing paved driveway runs from the street along the ridge to the house.

The adjoining lots on either side are currently developed with houses of similar locations and sizes. The house portion of the site is mapped in the 1973 Soil Survey for Anne Arundel County, Maryland with the well-drained Monmouth fine sandy loam, 15-40% slopes (MvE) mapping unit. However, the ridge top is much less steep and all proposed improvements are located on slopes less than 15%.

A site investigation was conducted on May 23, 2005, by Eric E. See of See Environmental Services, Inc. No plant species were observed that are considered rare, threatened or endangered by the U.S. Fish & Wildlife Service or the Maryland Department of Natural Resources (DNR).

III. Proposed Conditions/Critical Area Compliance

There is 0.39 acre of impervious coverage. Construction of the proposed house addition and changes to the driveway and garage would create a total of 0.375 acre, or 3.9% of the site, well under the 15% maximum allowed in LDA.

Tree cover (forest and developed woodlands: tress over mowed lawn and ornamental plantings) is approximately 3.5 acres. Proposed clearing of individual trees around the existing house would be approximately 3,000 square feet (based on estimated canopy area estimated by DBH of trees proposed to be removed). This would be well under the 20% allowed in RCA with 1-to-1 replacement required.

Stormwater management is proposed as additional plantings and rooftop disconnection. Sediment control measures will be developed at time of Grading Permit, and may include use of super silt/reinforced silt fence.

IV. Variance Standards:

Because the entire ridge top on which the existing house sites is in the Expanded Buffer, no exterior additions or improvements can occur without a variance.


With stormwater management and sediment controls during construction and with reforestation provided by on-site replacement, construction of the proposed house should be able to completed without significant impacts to water quality and fish and wildlife habitat.

References

Anne Arundel County PACE. Critical Area Map #24.

Bay Engineering, Inc., 2005 site plans and field surveys.

Soil Conservation Service, 1967. Soil Survey for Anne Arundel County, Maryland. USDA.





Architecture Planning
Interior Design

October 7, 2005 Revised October 10, 2005 Revised is in Italics

Mr:Stephen LeGendre, Hearing Officer Administrative Hearing Office 44 Calvert St. Annapolis, MD 21401

Re: Variance 2005-297 Erik Young

Dear Mr. LeGendre:

We appreciate your willingness to accept the revised application for the variance stated above. The owner has worked diligently with Critical Area Commission and the County over the past week to minimize impacts in the buffer and to decrease impervious below what is existing on site This revised proposal has reduced impervious to 13,042 sq. ft. (6.9%). Existing on site is 14,080 s. f. (7.48%). On Friday, October 7, Liz West in consultation with Bill Love requested a modification to the expanded Buffer. Revised Exibit 2,3 and4 reflect thus changs. Therefore, the impervious in the buffer has been changed to 3,537.

Enclosed heated footprint of the proposed house is 2,918 compared to 2,228 of the existing house. The enclosed ground floor footprint contains a master bedroom suite; existing patios with steps have been replaced with covered porches to minimize steps. The garage is attached to the main house to create a covered mobstrocted path of travel. These programatic requirements are to accommodate the owner's wife who is legally blind. This revised proposal reduces the garage to a standard two car garage and the link to the house has been reduced. Four documents are enclosed that illustrate the revised plan are enclosed.

1. A colored site plan showing the existing impervious

2. A colored site plan showing the reductions as recommended by Critical Area Commission.

3. Site tabulation sheet

4. Overall site plan

5. Letter from Owner's Physician


We greatly appreciate your time and consideration of this revised proposal.

Sincerely yours

Concu Breeding, Principal


Cc. Liz West, Gary Evans, Erik Young

ALT BREEDING SCHWARZ, ILC 209 MAIN STREET ANIAPOLIS, MARYLAND 21401 410:268.1213 PAX 410.268.2965 WWW.absrichitects.com



12/

VARIANCE 2005-297



OCTOBERIO, 2005 ABS ARCHITECTS

ENLARGED VIEW

SCALE: 1"=20'

EXH1817 - 2-



IMPERVIOUS TOBE DELETED
AS RECOMMENDED BY
CRITICAL AREA COMMISSION

Exhibit 3

Revised October 10, 2005

Site Tabulations 870 Child's Point Road

Total Site Area:


188,307 SF

	Existing	Application Proposed	Revised, as per meeting with Critical Area
House	2,228 SF	2,954 SF	2,918 SF
Porches	0 SF	773 SF	773 SP
Walks	1060 SF	1,885 SF	455 SF
Garage and Slab	759 SF	1,021 SF	713 SP
Drive	9,728 SF	9,361 SF	8,183 SF
Patio (Shed)	100 SF	0 SF	0 SP
TOTAL	14,080 SF	15,994 SP ⁱⁱ	13,042 SF
Percentage	7.48	8.5	6.9
/Impervious in Buffer	2,806 SF		3,537 SF*

¹ Site visit corrected walkway sq. footage.

Revised total correcting addition.

Revised as requested by Anne Armodel County.






EXHIBIT 5

Edward Tsoy, M.D.

9707 Medical Center Drive Suite 110 Rockville, MD 20850 (301) 424-7744

October 5, 2005

Steve Legendre, Esq. Administrative Hearing Office 44 Calvert Street Annapolis, MD 21401

Re: Joyce Young's Visual Disability

Dear Mr. Legendre:

I have cared for Mrs. Joyce Young since 1988. In addition to the care I provided her, she receives care from a retinal specialist at the Wilmer Eye Clinic at Johns Hopkins University. Mrs. Young suffers from retinitis pigmentosa. This condition is a progressive, degenerative disease of the retina which is characterized by a gradual loss of peripheral vision and the ability to see in darkness. It is an inherited disorder and in the case of Mrs. Young, her father, several of her siblings, and several of her nieces and nephews are affected. In addition, presence of the disease has not been ruled out in all of her children. Mrs. Young has been symptomatic with this disease since her early twenty's and her symptoms have progressed to the point that at this time she can no longer drive, she has a significant loss of her peripheral vision, and she has night blindness. Given the fact that her father is totally blind and other family members are severely affected by this disease, it is likely that Mrs. Young will be become totally blind in the future.

With this in mind, it is very appropriate that in the course of designing a new residence, she and her husband wish to placed the master suite on the first floor and orient the house toward the South and Southwest so that the common living areas will be well lit with natural sunlight.

Sincerely yours

Edward Tsoy, M.D.

Fellow, American Academy of Ophthalmology



October 5, 2005

Ms. Regina Essingler State of Maryland Critical Area Commission 1804 West Street, Suite 100 Annapolis, Maryland 21401 Architecture • Planning Interior Design

Re: Variance 2005-0297-V Erik Young

Dear Ms. Essingler,

Thank you for meeting with Dr. Young, Gary Evans and myself yesterday to discuss this application for variance.

Based on our discussion, we understood that you were basically comfortable with the orientation and the footprint of the house but would like to see reduction in size of the driveway and the size of the garage to reduce the overall impacts.

Enclosed please find a copy of modifications we have made to minimize impacts. The garage is reduced to a standard two car garage - 40' to 26'; - the link between the house and the garage is reduced by 1'-6; the walkways are reduced by changing hardscape to mulch; the driveway is reduced to 12 ft. in width. This reduces the overall proposed impervious coverage to 6.9% of the site area. This number is less than the 7.48% existing impervious coverage.

We sincerely appreciate your willingness to review this revised plan promptly and your cooperation in getting a revised opinion letter to the County. The Hearing Officer has asked that we delivery the entire revision package to him by noon on Friday, October 7, 2005. Please call should you have questions.

Since ely yours,

Scarlett Breeding, Principal

Cc: Lois Vilamaire, Dr. Erik Young, Gary Evans

Enclosure

RECEIVED

OCT 06 2005

CRITICAL AREA COMMISSION

ALT BREEDING SCHWARZ, LLC 209 MAIN STREET ANNAPOLIS, MARYLAND 21401 410.268.1213 FAX 410.268.2965 www.absarchitects.com

Site Tabulations 870 Child's Point Road

Total Site Area:

188,307 SF

	Existing	Application Proposed	Revised, as per meeting with Critical Area
House	2,228 SF	2,954 SF	2,918 SF
Porches	0 SF	773 SF	773 SF
Walks	1060 SF ⁱ	1,885 SF	455 SF
Garage and Slab	759 SF	1,021 SF	713 SF
Drive	9,728 SF	9,361 SF	8,183 SF
Patio (Shed)	100 SF	0 SF	0 SF
TOTAL	14,080 SF	15,994 SF ⁱⁱ	13,042 SF
Percentage	7.48	8.5	6.9

3631

RECEIVED

OCT 06 2005

CRITICAL AREA COMMISSION

ⁱ Site visit corrected walkway sq. footage. ⁱⁱ Revised total correcting addition.

Site Tabulations

Total Site Area: 188,307 SF Slopes 15% or Greater: 113,705 SF Ex. Impervious Cover:

	Existing	Proposed
House	2,228 SF	2,954 SF
Garage	759 SF	1,021 SF
Porches	0 SF	773 SF
Drive	9,728 SF	9,361 SF
Walks	2,521 SF	1,885 SF
Shed	100 SF	0 SF
TOTAL	15,987 SF	18,105 SF
Percentage	8.5	9.6

RECEIVED

OCT 0 4 2005

CRITICAL AREA COMMISSION

EXHIBIT #6 SITE TABULATIONS 870 CHILD'S POINT ROAD

HOUSE
PORCH
WALKS & PATIO
GARAGE & CONCRETE SLAB
DRIVEWAY
POND
DECK*
TOTAL
*Considered impossions due to et ere

EXISTING						
IMPERVIOUS AREA (SQ FT)						
OUTSIDE						
W/IN BUFFER	BUFFER	TOTAL				
1,612	29	1,641				
58	43	101				
959	338	1,297				
	618	618				
	8,907	8,907				
79		79				
255		255				
2,963	9,935	12,898 OR 6.9%				


PROPOSED							
IMPI	IMPERVIOUS AREA (SQ FT)						
W/IN BUFFER BUFFER TOTAL							
1,608	1,220	2,828					
	215	215					
307	93	400					
	734	734					
	8,067	8,067					
1,915	10,329	12,244 OR 6.5%					

TOTAL SITE AREA = 188,307 SQ FT

1048 & reduction in Buffer

1742 4 = footprint of waiting house

^{*}Considered impervious due to at-grade deck



± 9,935 SF EXISTING IMPERVIOUS OUTSIDE BUFFER

PARTIAL SITE PLAN


SCALE: 1"=20'

EXHIBIT #2



Steep Slopes 25% Or Greater





± 10,329 SF PROPOSED IMPERVIOUS OUTSIDE BUFFER

PARTIAL SITE PLAN


SCALE: 1"=20'

EXHIBIT #3



Steep Slopes 25% Or Greater







± 1,818 SF EXIST. IMPERVIOUS REMOVED IN BUFFER

 \pm 958 SF EXIST. IMPERVIOUS REMOVED OUTSIDE BUFFER

EXISTING IMPERVIOUS TO BE REMOVED

PARTIAL SITE PLAN

SCALE: 1"=20'


EXHIBIT #4

Information provided by Bay Engineering Inc.



Steep Slopes 25% Or Greater





PROPOSED IMPERVIOUS TO REMAIN OR BE RE-USED

PROPOSED IMPERVIOUS TO BE ADDED

NET REDUCTION OF IMPERVIOUS AREA IN BUFFER: ± 1,048 SF

REDUCTION OF IMPERVIOUS IN BUFFER

PARTIAL SITE PLAN

SCALE: 1"=20'

EXHIBIT #5

Information provided by Bay Engineering Inc.



Steep Slopes 25% Or Greater



TO REVIEW THE APPROVED PLANS. (1 DAY) 2. INSTALL S.C.E. AND SILT FENCE AS SHOWN ON THE PLAN, PROTECT EXISTING UTILITIES. (5 DAYS)

3. DEMO EXISTING HOUSE AND PREPARE SITE FOR NEW HOUSE. (4 WEEKS) 4. EXCAVATE FOR FOOTERS AND FOUNDATION. BEGIN HOUSE CONSTRUCTION AND EARTHWORK. (2 MONTHS) 5. RECONNECT UTILITIES, INSTALL SEPTIC (1 MONTH)

6. FINISH CONSTRUCTION OF HOUSE. (3 MONTHS) 7. FINE GRADE, FINAL PAVE WALKS AND DRIVE. (3 WEEKS) 8. INSTALL PLANTINGS FOR STORM WATER MANAGEMENT. (14 DAYS)

9. STABILIZE ALL DISTURBED AREAS WITH SEED AND MULCH AS SPECIFIED. WITH THE INSPECTORS

APPROVAL REMOVE ANY REMAINING SEDIMENT CONTROL DEVICES. (9 DAYS) 10. FINAL CLEAN UP BY DEVELOPER AND ONGING MAINTENANCE BY THE OWNERS.

STANDARD RESPONSIBILITY NOTES

I (WE) CERTIFY THAT:

A. ALL DEVELOPMENT AND CONSTRUCTION WILL BE DONE IN ACCORDANCE WITH THIS SEDIMENT AND EROSION CONTROL PLAN, AND FURTHER, AUTHORIZE THE RIGHT OF ENTRY FOR PERIODIC ON-SITE EVALUATION BY THE ANNE ARUNDEL SOIL CONSERVATION DISTRICT BOARD OF SUPERVISORS OR THEIR AUTHORIZED AGENTS.

B. ANY RESPONSIBLE PERSONNEL INVOLVED IN THE CONSTRUCTION PROJECT WILL HAVE A CERTIFICATE OF ATTENDANCE FROM THE MARYLAND DEPARTMENT OF THE ENVIRONMENT'S APPROVED TRAINING PROGRAM FOR THE CONTROL OF SEDIMENT AND EROSION BEFORE BEGINNING THE PROJECT.

RESPONSIBLE PERSON ON-SITE: TO BE DETERMINED

C. IF APPLICABLE, THE APPROPRIATE ENCLOSURE WILL BE CONSTRUCTED AND MAINTAINED ON SEDIMENT BASIN(S) INCLUDED IN THIS PLAN. SUCH STRUCTURE(S) WILL BE IN COMPLIANCE WITH THE ANNE ARUNDEL COUNTY CODE.

2. THE DEVELOPER IS RESPONSIBLE FOR THE ACQUISITION OF ALL EASEMENTS, RIGHT, AND/OR RIGHTS-OF-WAY THAT MAY BE REQUIRED FOR THE SEDIMENT AND EROSION CONTROL PRACTICES, STORMWATER MANAGEMENT PRACTICES AND THE DISCHARGE OF STORMWATER ONTO OR ACROSS ADJANCENT OR DOWNSTREAM PROPERTIES INCLUDED IN THE PLAN.

3. INITIAL SOIL DISTURBANCE OR REDISTURBANCE, PERMANENT STABILIZATION SHALL BE COMPLETED WITHIN SEVEN CALENDAR DAYS FOR THE SURFACE OF ALL CONTROLS, DIKES, SWALES, DITCHES, PERIMETER SLOPES, AND ALL SLOPES GREATER THAN 3 HORIZONTAL TO 1 VERTICAL (3:1) AND FOURTEEN DAYS FOR ALL OTHER DISTURBED OR GRADED AREAS ON THE PROJECT SITE. TEMPORARY STABILIZATION OF THE SURFACE OF PERIMETER CONTROLS, DIKES, SWALES, DITCHES, AND PERIMETER SLOPES MAY BE ALLOWED AT THE DISCRETION OF THE SEDIMENT CONTROL INSPECTOR.

4. THE SEDIMENT CONTROL APPROVALS ON THIS PLAN EXTEND ONLY TO AREAS AND PRACTICES IDENTIFIED AS PROPOSED WORK.

5. THE APPROVAL OF THIS PLAN FOR SEDIMENT AND EROSION CONTROL PLAN DOES NOT RELIEVE THE DEVELOPER/CONSULTANT FROM COMPLYING WITH ANY FEDERAL, STATE OR COUNTY REQUIREMENTS APPERTAINING TO ENVIRONMENTAL ISSUES.

6. THE DEVELOPER MUST REQUEST THAT THE SEDIMENT CONTROL INSPECTOR APPROVE WORK COMPLETED IN ACCORDANCE WITH THE APPROVED EROSION AND SEDIMENT CONTROL PLAN, THE GRADING OR BUILDING PERMIT, AND THE ORDINANCE.

7. ALL MATERIAL SHALL BE TAKEN TO A SITE WITH AN APPROVED SEDIMENT AND EROSION CONTROL PLAN

8. ON ALL SITES WITH DISTURBED AREAS IN EXCESS OF 2 ACRES, APPROVAL OF THE SEDIMENT AND FROSION CONTROL INSPECTOR SHALL BE REQUIRED ON COMPLETION OF INSTALLATION OF PERIMETER EROSION AND SEDIMENT CONTROLS, BUT BEFORE PROCEEDING WITH ANY OTHER EARTH DISTURBANCE OR GRADING. OTHER BUILDING OR GRADING INSPECTION APPROVALS MAY NOT BE AUTHORIZED UNTIL THE INITIAL APPROVAL BY THE SEDIMENT AND EROSION CONTROL INSPECTOR IS GIVEN.

9. APPROVAL SHALL BE REQUESTED ON FINAL STABILIZATION OF ALL SITES WITH DISTURBED AREAS IN EXCESS OF 2 ACRES BEFORE REMOVAL OF CONTROLS.

10. EXISTING TOPOGRAPHY MUST BE FIELD VERIFIED BY RESPONSIBLE PERSONNEL TO THE SATISFACTION OF THE SEDIMENT CONTROL INSPECTOR PRIOR TO COMMENCING WORK.

SIGNATURE OF DEVELOPER/OWNER DATE

> TITLE: OWNER AFFILIATION: N/A ADDRESS: 15005 SHADY GROVE ROAD, SUITE 350, ROCKVILLE MD 20850 TELEPHONE NUMBER: 301-424-4803

CONSULTANT'S CERTIFICATION

NAME: ERIK B. YOUNG

"THE DEVELOPER'S PLAN TO CONTROL SILT AND EROSION IS ADEQUATE TO CONTAIN THE SILT AND EROSION ON THE PROPERTY COVERED BY THIS PLAN. I CERTIFY THAT THIS PLAN OF EROSION AND SEDMENT CONTROL REPRESENTS A PRACTICAL AND WORKABLE PLAN BASED ON MY PERSONAL KNOWLEDGE OF THIS SITE, AND WAS PREPARED IN ACCORDANCE WITH THE REQUIREMENTS OF THE ANNE ARUNDEL SOIL CONSERVATION DISTRICT PLAN SUBMITTAL GUIDELINES AND THE CURRENT MARY AND STANDARDS AND SPECIFICATIONS OF SEDIMENT AND PROSION CONTROL I HAVE REVIEWED THIS PROSION SEDIMENT CONTROL PLAN WITH THE OWNER/DEVELOPER."

BY: JOHN E. SCOTT III, P.E. BAY ENGINEERING, INC. MARYLAND REGISTERED PROFESSIONAL ENGINEER # 16084

POST DEVELOPMENT OWNER/DEVELOPER'S STABILIZATION CERTIFICATION

"ALL GRADING DRAINAGE STRUCTURES AND/OR SYSTEMS, EROSION AND SEDIMENT CONTROL PRACTICES INCLUDING FACILITIES AND VEGETATIVE MEASURES HAVE BEEN COMPLETED IN CONFORMANCE WITH THE APPROVED PLANS AND SPECIFICATIONS".

OWNER/DEVELOPER

STORMWATER MANAGEMENT RECORD DRAWING CERTIFICATION

DATE

THIS CERTIFIES TO THE BEST OF MY PROFESSIONAL BELIEF AND KNOWLEDGE, THE APPROVEDS.W.M. SYSTEM(S) AS SHOWN HEREON HAVE BEEN CONSTRUCTED IN SUCH A MANNER THAT WOULD BE CONSISTENT WITH THE APPROVED PLANS. ANY CHANGES/MODIFICATIONS ARE IDENTIFIED IN RED.

JOHN E. SCOTT III, P.E.# 16084

LEGEND

PROPERTY LINE / RIGHT-OF-WAY **EXISTING CONTOUR**

EXISTING SPOT ELEVATION

EXISTING WOODS LINE EXISTING TREE / TREE TO BE REMOVED

EXISTING ZONING DESIGNATION EXISTING UTILITY POLE W/ OVERHEAD WIRE

100' BUFFER -

OVERALL SITE AREA AND DRAINAGE AREA MAP

TOPO: A.A.Co., D.P.W.

THE SITE IS 4.3 ACRES AND IS TIDAL WATERS. THE

THE APPLICANT IS SEEKING A VARIANCE TO DISTURB

OUTFALL STATEMENT

VARIANCE STATEMENT

AREAS WITHIN THE EXPANDED BUFFER.

WATERFRONT IS STABLE WITH NO EROSIVE

211F


CHURCH CREEK

TOTAL SITE AREA

188,307.2 S.F.

D.A.= 4.323 AC.

EXISTING FENCE



EXISTING SEWER

PROPOSED CONTOUR PROPOSED SPOT ELEVATION PROPOSED WOODS LINE

LIMIT OF DISTURBANCE REINFORCED SILT FENCE _____ SS _____ SS ____ _210.00 $\sim\sim\sim\sim\sim$

VICINITY MAP

SCALE: 1" = 2000' COPYRIGHT ADC THE MAP PEOPLE PERMITTED USE NO. 20400770

GENERAL NOTES

PURPOSE STATEMENT: THE PURPOSE OF THESE PLANS IS TO REFLECT THE EXISTING AND PROPOSED SITE CONDITIONS FOR REPLACING A SINGLE FAMILY HOME ON LOT 9, 'BYWATER ESTATES'.

1.) ALL SITE WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST EDITIONS OF THE ANNE ARUNDEL COUNTY DEPARTMENT OF PUBLIC WORKS REQUIREMENTS AND SPECIFICATIONS UNLESS OTHERWISE DETAILED OR SPECIFIED ON

2.) THE EXISTING UTILITIES AND OBSTRUCTIONS SHOWN ARE FROM THE BEST AVAILABLE RECORDS AND SHALL BE FIELD VERIFIED BY THE CONTRACTOR TO HIS OWN SATISFACTION PRIOR TO ANY CONSTRUCTION. ANY UTILITIES DAMAGED DUE TO THE CONTRACTORS NEGLIGENCE SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR'S EXPENSE.

3.) THE CONTRACTOR SHALL CALL "MISS UTILITY" (1-800-257-7777) A MINIMUM OF 5 DAYS IN ADVANCE OF ANY CONSTRUCTION AND /OR EXCAVATION. 4.) THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING ANY FENCE, DRIVEWAY, LANDSCAPING, ETC. DAMAGED OR

REMOVED BY HIM DURING CONSTRUCTION. ALL DISTURBED AREAS OUTSIDE THE RIGHT OF WAY LINES SHALL BE RETURNED TO THEIR ORIGINAL CONDITION UNLESS OTHERWISE INDICATED AND SPECIFIED. 5.) IT SHALL BE DISTINCTLY UNDERSTOOD THAT FAILURE TO MENTION SPECIFICALLY ANY WORK THAT WOULD NATURALLY

6.) THESE DRAWINGS DO NOT INCLUDE THE NECESSARY COMPONENTS FOR CONSTRUCTION SAFETY. ALL CONSTRUCTION

MUST BE DONE IN COMPLIANCE WITH THE LATEST VERSION OF OSHA STANDARDS AND/OR REGULATIONS.

BE REQUIRED TO COMPLETE THE PROJECT SHALL NOT RELIEVE THE CONTRACTOR OF HIS RESPONSIBILITY TO PERFORM

7.) IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY THE ENGINEER OF ANY DEVIATION TO THIS PLAN PRIOR TO ANY CHANGE BEING MADE. ANY CHANGE IN THIS PLAN MADE WITHOUT THE WRITTEN AUTHORIZATION FOR SAID CHANGE FROM THE ENGINEER SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR OR THE SUBCONTRACTOR. SAID CHANGES MAY WARRANT COUNTY REVIEW AND APPROVAL.

8.) THE CONTRACTOR SHALL NOTE THAT IN THE CASE OF A DISCREPANCY BETWEEN THE SCALED AND THE FIGURED DIMENSIONS SHOWN ON THESE PLANS, THE FIGURED DIMENSION SHALL GOVERN.

9.) THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION OF HIS CONSTRUCTION WITH THE CONSTRUCTION BY OTHER CONTRACTORS, SUBCONTRACTORS.

10.) IF NECESSARY, ALL UTILITY POLES SHALL BE BRACED WHEN NECESSARY AT THE CONTRACTORS EXPENSE. THE UTILITY POLES SHALL BE RELOCATED AT THE OWNER'S EXPENSE ONLY IN CASES WHERE THEY WILL INTERFERE WITH

11.) ALL AVAILABLE UTILITIES (IE., ELECTRIC, WATER, GAS, AND COMMUNICATIONS) SHALL BE PROVIDED FROM EXISTING ADJACENT FACILITIES AND IN ACCORDANCE WI H THE UTILITY COMPANY REQUIREMENTS.

12.) THE CONTRACTOR IS CAUTIONED THAT UNDERGROUND CABLES MAY EXIST IN THE PUBLIC RIGHT OF WAY AND BEYOND. WORK IN AND OUT OF THE RIGHT OF WAY SHOULD NOT BEGIN UNTIL THE CONTRACTOR IS FAMILIAR WITH THE LOCATION AND DEPTH OF CABLES. ANY DAMAGE TO EXISTING UTILITY SERVICES SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR COST.

13.) JOB SAFETY IS THE SOLE THE RESPONSIBILITY OF THE CONTRACTOR, SUBCONTRACTORS AND VENDORS.

14.) THE SITE IS SERVED BY PRIVATE WELL AND PRIVATE SEPTIC. THE CONTRACTOR SHALL VERIFY THE LOCATION OF THE EXISTING SERVICES, FILE RE-CONNECTION APPLICATIONS AND PERFORM CONNECTIONS.

15.) ALL STRUCTURAL FILL SHALL BE PLACED IN 8" LOOSE LAYERS AND COMPACTED TO 95 % MAXIMUM DRY DENSITY AT OPTIMUM MOISTURE CONTENT AS DETERMINED BY AASHTO T-180 METHOD. THE CONTRACTOR SHALL USE CLASS I SELECT MATERIALS FOR THE FOOTINGS FOUNDATIONS AND BACK FILL FOR ALL FOUNDATION AND RETAINING WALLS.

16.) THE TOPOGRAPHIC INFORMATION SHOWN ON THE SITE PLAN WAS DERIVED FROM SURVEY PREPARED BY BAY ENGINEERING, INC., APRIL, 2005.

17.) THE ELEVATIONS OF THE FLOOD ZONE WERE OBTAINED FROM FEMA MAPS. PORTIONS OF THIS SITE ARE LOCATED WITHIN A FEMA FLOOD ZONE A6 (ELE 7) AND C, MAP #240008 0038 D, PANEL 38 OF 61.

18.) THE UNITED STATES DEPARTMENT OF AGRICULTURE SOIL SURVEY REVIEWED ON FILE WITH ANNE ARUNDEL COUNTY SOIL CONSERVATION DISTRICT INDICATED THAT THE MAJOR SOIL CLASSIFICATION IS MVE, MONMOUTH FINE SANDY LOAM AS PER MAP 27 OF SOIL SURVEY OF A.A.CO., MD.

19.) ALL ROOF DRAINS SHALL BE DISCHARGED ONTO SPLASH BLOCKS.

20.) ZONING IS R1/RCA YARDS AND SETBACKS: FRONT 30, SIDE 7/20 COMBINED, REAR 25.

TOTAL SPOIL TO BE PLACED ONSITE IS 0 CUBIC YARDS.

21.) SITE PLAN TABULATIONS: TOTAL SITE AREA: 188,307 SF OR 4.323 ACRES TOTAL DISTURBED AREA 232,322 SF OR 0.512 ACRES EXISTING IMPERVIOUS COVERAGE IS 15,987 SF PROPOSED IMPERVIOUS COVERAGE: 15,994 SF OR 0.375 ACRES IMPERVIOUS COVERAGE PERMITTED IS 15 % OR 28,246 SF TOTAL AREA VEGETATIVELY STABILIZED IS 6,328 SF OR 0.145 ACRES. TOTAL AREA STRUCTURALLY STABILIZED IS 15,994 SF OR 0.375 ACRES. TOTAL CUT ON SITE IS 110 CUBIC YARDS TOTAL FILL ON SITE IS 110 CUBIC YARDS

TOTAL BORROW TO BE BROUGHT TO THE SITE IS 0 CUBIC YARDS.

22.) NO BOUNDARY SURVEY WAS PERFORMED BY BAY ENGINEERING, INC. AT THIS TIME. THIS PLAN WAS PREPARED WITHOUT BENEFIT OF A TITLE REPORT, WHICH MAY SHOW ADDITIONAL CONVEYANCES, EASEMENTS, COVENANTS, RIGHT OF WAYS OR MORE STRINGENT BUILDING RESTRICTIONS NOT SHOWN HEREON.

23.) THE SITE IS MAPPED NON-BUFFER EXEMPT AS MAP 51 OF CRITICAL AREA OVERLAY.

PERMIT INFORMATION

GRADING PERMIT #: G02 BUILDING PERMIT #:B02_ VARIANCE CASE #: PERC. APPLICATION #: T02033599

1 OF 4

2 OF 4

3 OF 4

4 OF 4

DRAWING INDEX

.....COVER SHEET, OVERALL D.A. MAP AND NOTES EXISTING CONDITIONS AND DEMOLITION PLAN SITE, GRADING AND SEDIMENT CONTROL PLAN DETAILS AND NOTES

District Official AASCD# - SMALL POND (S) # N/A Reviewed for technical adequacy by USDA, Natural Resources Conservation Service

THIS SITE IS NOT WITHIN THE SEVERN RIVER WATERSHED

Anne Arundel Soil Conservation District

Sediment and Erosion Control Approva

8

JULY 25, 2005 05-1562 Scale AS SHOWN Drawn By Designed By Approved By

Folder Reference YOUNG ERIK CHILD POINT

ATE

BYW. 9 0


SEP 08 2005

L AREA COMMISSION

1 OF 4 05-1562 File No.



SEP 0 8 2005 2 OF 4 05-1562



SECOND DISTRICT ANNE ARUNDEL COUNTY

File: P:\Young Erik MD 870 Childs Point 05-1562\Drawing Files\05-1562 GP SHT 2.di

05-156

SEP 0 8 2005

CAL AREA COMMISSION

No. 1 OF 1

0. 05-1562

Following initial soil disturbances or redisturbance, permanent or temporary stabilization shall be completed within seven calendar days fort he surface of all perimeter controls, dikes, swales, ditches, perimeter slopes, and all slopes grater than 3 horizontal to 1 vertical (3:1) and fourteen days for all other disturbed or graded areas on the project site.

1. Permanent Seeding:

A. Soil Tests: Lime and fertilizer will be applied per soll tests results for sites greater than 5 acres. Soil tests will be done at completion of initial rough grading or as recommended by the sediment control inspector. Rates and analyses will be provided to the grading inspector as well as the contractor.

1. Occurrence of acid sulfate solls (grayish black color) will require covering with a minimum of 12 inches of clean soil with 6 inches minimum capping of top soil. No stockpiling of material is allowed. If needed, soll tests should be done before and after a 6-week incubation period to allow oxidation of sulfates.

The Minimum soil conditions required for permanent vegetative establishment are: a. Soil pH shall be between 6.0 and 7.0

b. Soluble salts shall be less than 500 parts per million (ppm). c. The soil shall contain less than 40 % clay but enough fine-grained material (> 30 % slit plus clay) to provide the capacity to hold a moderate amount of moisture. An exception Is if lovegrass or serecia lespedeza is to be planted, then a sandy soil (< 30 % slit plus clay) would

d. Soil shall contain 1.5% minimum organic matter by weight. e. Soil must contain sufficient pore space to permit adequate root penetration.

f. If these conditions cannot be met by solls on site, adding topsoll is regulred in accordance with Section 21 Standard and Specification for Topsoil or amendments made as recommended by a certified agronomist.

B. Seedbed Preparation: Area to be seeded shall be loose and friable to a depth of at least 3 inches. The top layer shall be loosened by raking, disking or other acceptable means before seeding occurs. For sites less than 5 acres, apply 100 pounds dolomitic limestone and 21 pounds of 10-10-10 fertilizers per 1,000 square feet. Harrow or disk lime and fertilizer into the soll to a depth of at least 3 inches on slopes flatter than 3:1.

C. Seeding: Apply 5-6 pounds per 1,000 square feet of tall fescue between February 1 and April 30 or between August 15 and October 31. Apply seed uniformly on a mist firm seedbed with a cyclone seeder, cultipacker seeder or hydroseeder (slurry includes seeds and fertilizer, recommended on steep slopes only). Maximum seed depth should be 1/4 Inch in clayey soils and 1/2 Inch sandy soils when using other than the hydroseeder method. Irrigate where necessary to support adequate growth until vegetation is firmly established. If other mixes are to be used, select from Table 25, entitled "Permanent Seeding For Low Maintenance Areas" from the current Standards and Specifications for Soil Erosion and Sediment Control. Mixes suitable for this are 1, 3 and 5-7. Mixes 5-7 are sultable in non-mowable situations.

D. Mulching: Mulch shall be applied to all seeded areas immediately after seeding. During the time periods when seeding is not permitted, mulch shall be applied immediately after grading.

Mulch shall be unrotted, unchopped, small grain straw applied at a rate of 2 tons per acre or 90 pounds per 1,000 square feet (2 bales). If a mulch-anchoring tool is used, apply 2.5 tons per acre. Mulch materials shall be relatively free of all kinds of weeds and shall be completely free of prohibited noxious weeds. Spread mulch uniformly, mechanically or by hand, to a depth of 1-2 Inches.

E. Securing Straw Mulch: Straw mulch shall be secured immediately following mulch application to minimize movement by wind or water. The following methods are permitted:

(i) Use a mulch-anchoring tool, which is designed to punch and anchor mulch into the soil surface to a minimum depth of 2 inches. This is the most effective method for securing mulch, however, it is limited to relatively flat areas where equipment can operate safely.

(ii) Wood cellulose fiber may be used for anchoring straw. Apply the fiber binder at a net dry weight of 750 pounds per acre. If mixed with water, use 50 pounds of wood cellulose fiber per 100 gallons of water.

(iii) Liquid binders may be used. Apply at higher rates at the edges where wind catches mulch, such as In valleys and in crests of slopes. The remainder of the area should appear uniform after binder application. Binders listed in the 1994 Standards and Specifications for Soil Erosion and Sediment Control or approved equal shall be applied at rates recommended by

(iv) Lightweight plastic netting may be used to secure mulch. The netting will be stapled to the ground according to manufacturer's recommendations.

2. Temporary Seeding:

Lime: 100 Pounds of dolomitic limestone per 1,000 square feet.

Fertilizer: 15 pounds of 10-10-10 per 1,000 square feet. Seed: Perennial rye-0.92 pounds per 1,000 square feet (February 1 through April 30 or

August 15 through November 1).

Millet-0.92 pounds per 1.000 square feet (May 1 through August 15)

Mulch: Same as 1 D and E. above.

3. No fills may be placed on frozen ground. All fill to be placed in approximately horizontal layers, each layer having a loose thickness of not more than 8 inches. All fill In roadways and parking areas is to be classified Type 2 as per Anne Arundel County Code -Article 21, Section 2-308, and compacted to 90 % density; compaction to be determined by ASTMD-1557-66T) (Modified Proctor). Any fill within the building area is to be compacted to a minimum of 95 % density as determined by methods previously mentioned. Fills for pond embankments shall be compacted as per MD-378 Construction Specifications. All other fills shall be compacted sufficiently so as to be stable and prevent erosion and slippage.

4. Permanent Sod:

Installation of sod should follow permanent seeding dates. Seedbed preparation for sod shall be as noted in section (B) above. Permanent sod is to be tall fescue, state approved sod; lime and fertilizer per permanent seeding specifications and lightly irrigate soll prior to laying sod. Sod is to be laid on the contour with all ends tightly abutting. Joints are to be staggered between rows. Water and roll or tamp sod to insure positive root contact with soil. All slopes steeper than 3:1, as shown, are to be permanently sodded or protected with approved erosion control netting. Additional watering for establishment may be regulred. Sod is not to be installed on frozen ground. Sod shall not be transplanted when moisture content (dry or wet) and/or extreme temperature may adversely affect its survival. In the absence of adequate rainfall, irrigation should be performed to ensure establishment of sod.

5. Mining Operations:

Sediment control plans for mining operations must include the following seeding dates and

For seeding dates of:

February 1 through April 30 and August 15 through October 31, use seed mixture of tall fescue at the rate of 2 pounds per 1,000 square feet and sericea lespedeza at the minimum rate of 0.5 pounds per 1,000 square feet.

6. Topsoil shall be applied as per the Standard and Specifications for Topsoil from the current Maryland Standards and Specifications for Soil Erosion and Sediment Control.

NOTE: Projects within 4 mlles of the BWI Airport will need to adhere to Maryland Aviation

NOTE: Use of this information does not preclude meeting all of the requirements of the current Maryland Standards and Specifications for Soil Erosion and Sediment Control.

Administration's seeding specification restrictions.

CALL "MISS UTILITY"

TELEPHONE 1-800-257-7777

FOR UTILITY LOCATION AT

LEAST 48 HOURS BEFORE

BEGINNING CONSTRUCTION.

1. All graded and disturbed areas including slopes shall be protected during cleaning and construction in accordance with the approved erosion and sediment control plan until they are adequately stabilized.

2. All erosion and sedlment control practices and measures shall be constructed, applied and maintained in accordance with the approved sediment control plan and all applicable Local, State, and Federal Standards and Specifications for Soll Erosion and Sediment Control.

3. Topsoll required for the establishment of vegetation shall be stockpiled in the amount necessary to complete finished grading of all exposed areas.

4. Areas to be filled shall be cleared, grubbed and stripped of topsoil, remove trees, vegetation, roots or other 5. Areas which are to be top soiled shall be scanfied to a minimum depth of three (3) inches prior to placement of

6. All fills shall be compacted to 95 % maximum density ASTM D-1557 (AASHTO T-180) Method-C at optimum moisture as required to reduce erosion, slippage, settlement, subsidence or other related problems. Fill intended

to support buildings, structures and conduits, etc. shall be compacted in accordance with above stated or local

requirements and codes, whichever are more stringent. 7. All fill shall be placed and compacted in layers not to exceed eight inches (8") in thickness.

8. Except for approved landfills or nonstructural fills, fill material shall be free of brush, rubbish, rocks, logs stumps, building debris and other objectionable materials that would interfere with, or prevent, construction of satisfactory

9. Frozen materials or soft, mucky or highly compressible materials shall not be incorporated into fill slopes or structural fills. Fill shall not be placed on a frozen foundation.


10. Groundwater, Seeps or springs encountered during construction shall be handled in accordance with the local Building Code, Standards and Specifications for Subsurface Drain or other approved methods. If conditions are staturated employ a design professional for foundation design and construction Inspections. Require a final certification after foundation cure period and prior to first floor decking is placed.

11. Stockpiles, borrow areas, and spoil areas shall be shown on the plans and shall be subject to the provisions of all applicable local, state, and federal Standard and Specifications.

12. Grade all disturbed areas with positive drainage at 2 % (percent) slope minimum.

13. Footers for building or house construction to be In virgin soil or on compacted soils designed and specified by a

14. Trees shall not be removed from building pad locations unless approval for building pad grading has been acquired or until such time as Grading plans for each lot are completed, submitted, and approved with each building permit application.



1-1/2 to 2" inch Surface Course 6" Base Course Or approved equal Subgrade must be tested and approved by a soils engineer prior to placement of final surface treatment

Sand subgrade to absorb surface drainage Compacted Sub-Grade 98% Dry Density If sub-grade is soft use a Geotextile or Fabric Barrier between subgrade and new stone drive

DRIVEWAY PAVING SECTION

OR APPROVED EQUAL FOR MATERIALS AND DEPTH

PERC APPLICATION No.: 102033599

PRIOR PERC(S): YES SOIL TYPE: MUCS MUGD SEWER SERVICE CATEGORY: RA WET SEASON RESTRICTED? TES IN NO HOUSE SIZE: OVER 3500 DATE TESTED: 3/3/05
PERSONS PRESENT SANITARIAN: PERSONS PRESENT

DURING TESTING:

Lin Africand Soft from Jones Mr. Teren and Son

TESTED IN WET SEASON? STES 10 NO 100 LDA 110A SOIL TEST RESULTS (slight)

Septic Tank 1500 gallon

Initial Drywell/Seepage Pit:

Replacement systems:

Total Depth feet


Total Depth 32 feet Diameter 8 feet No. of Pits 3


Diameter feet No. of Pits Pits Separated by 24 feet from edge to edge


Pits Separated by feet from edge to edge

SHOW DRYWELLS IN AREA OF TEST 5, SHOW A 3600 SQ. FOOT MOUND IN AREA OF TESTS 1&4.SHOW 1' TOPO IN MOUND AREA.SHOW SYSTEM 25' FROM 25% SLOPE.EXISTING DUG WELL MUST BE ABANDONED. AN APPROVED NITROGEN REDUCING UNIT IS REQUIRED DUE TO CRITICAL AREA, NO VARIANCES TO SIZING OR REPLACEMENTS WILL BE ALLOWED

The above recommendations are for a house larger than 3500 square feet and does not constitute Health Department approval of the site.







AFFORESTATION NOTE

THE SITE PRESENTLY CONTAINS 112,841 SQ. FT. OF WOODLAND COVER. THE APPLICANT MUST HAVE 15% OF THE SITE FORESTED IN ADDITION TO SWM PLANTINGS. NO ACTION IS REQUIRED FOR AFFORESTATION.

REFORESTATION NOTE

UNDER THIS PLAN THE APPLICANT MUST CLEAR 2,198 SQ. FT. OF WOODLAND COVER TO DEVELOPE THIS SITE. THE APPLICANT MUST MITIGATE FOR THIS REMOVAL AT A 2:1 RATIO. 2,198 / 400 = 5.5 X 2 = 11 TREES AND 33 SHRUBS.

REFORESTATION PLANT LIST:

QTY COMMON NAME BOTAINICAL NAME 11 OGM Maple, October Acer Rubrum Glory 2-1/2 cal.

Spicebush

Cont. 6'-16'

Plant materials may be changed in accordance with materials listed by AACO, locations may be changed in the field to suit conditions.

Lindera benzoin

STORMWATER MANAGEMENT NOTE

The proposed developement offers an increase of 7 sq. ft. of impervious coverage. To address storm water management we have chosen plantings equal the proposed increase of coverage. This formula requires the installation of 1 trees and 3 shrubs. Please refer to the planting schedule for the material specifications.

SYMBOL

STORMWATER PLANT LIST:

Plant List: QTY COMMON NAME **BOTAINICAL NAME** 4 OGM Maple, October Acer Rubrum Glory 2-1/2 cal.


be changed in the field to suit conditions.

Spicebush

12 SB

Cont. 6'-16' Plant materials may be changed in accordance with materials listed by AACO, locations may

Lindera benzoin



ineering

ह JULY 25, 2005 **Job Number** 05-1562

Scale AS SHOWN Drawn By Designed By Approved By J.E.S.

> **Folder Reference** YOUNG ERIK CHILD POINT

BYWATER

9 0

05-1562

File No.

TAX MAP

ANNAPOLIS, MD 21401

CHILDS POINT ROAD ANNAPOLIS, MD 21401

874 CHILDS POINT ROAD

T.M. 51, G. 21, P. 174, LOT 1 873 CHILDS POINT ROAD

ANNAPOLIS, MD 21401

ANNAPOLIS, MD 21401

869 CHILDS POINT ROAD ANNAPOLIS, MD 21401

859 CHILDS POINT ROAD ANNAPOLIS, MD 21401

T.M. 51, G. 21, P. 173

T.M. 51, G. 21, P. 169, P/O LOT 9


VARIANCE PLANS

OF THE

870 CHILDS POINT ROAD AN R1/RCA SINGLE LOT GRADING PERMIT

LOT9; BYWATER ESTATES


GROUP '82', PLAT REF 19/26 TAX MAP 51, GRID 21, PARCEL 169 TAX ACCOUNT #02-145-01867400 DEED 16301 / 0199 SECOND DISTRICT ANNE ARUNDEL COUNTY



CRITICAL AREA COMMISSION DEC 6 2005



VICINITY MAP



gincering Inc. Planners and Surveyors

3

NOVEMBER, 2005 Job Number 05-1562 AS SHOWN Drawn By

Approved By T. SCHUMAN

L. SQUIRES

Folder Reference YOUNG, ERIK CHILD'S POINT, BYWATER ESTATES

SITE LEGEND

CRITICAL AREA COMMISSION

DEC e zono

BECEINED

PROPERTY OWNERS LIST

ANNAPOLIS, MD 21401

ANNAPOLIS, MD 21401

C/O AMY SOLAN

BARRY & DIANA LEVINSON

8440 SANDERLING ROAD

SARASOTA, FL 34242

ANNAPOLIS, MD 21401

JAMES & CRYSTLE SEARS

· CALLALLAND.

8306 WILSHIRE BLVD. PMB 1012

EXISTING SLOPES 15% TO 25% **EXISTING SLOPES GREATER THAN 25% EXISTING WOODS**

PROPERTY LINE / RIGHT-OF-WAY

EXISTING CONTOUR

EXISTING FENCE

EXISTING TREE / TREE TO BE REMOVED **EXISTING SOILS BOUNDARY**

EXISTING UTILITY POLE W/ OVERHEAD WIRE EXISTING WATER

EXISTING CHESAPEAKE BAY 100' BUFFER

EXISTING EXPANDED CHESAPEAKE BAY BUFFER **EXISTING SEWER EXISTING STORM DRAIN**

EXISTING PERC TEST LOCATION **EXISTING ZONING DESIGNATION**

EXISTING SOILS DESIGNATION

PROPOSED WATER PROPOSED SEWER PROPOSED STORM DRAIN PROPOSED CONCRETE

PROPOSED CONTOUR PROPOSED SPOT ELEVATION

PROPOSED BITUMINOUS PAVEMENT TO BE REMOVED

TO BE ABANDONED STABILIZED CONSTRUCTION ENTRANCE

REINFORCED SILT FENCE SUPER SILT FENCE LIMIT OF DISTURBANCE

+ 30x50

CRITICAL AREA COMMISSION

GENERAL NOTES

5. THE EXISTING ZONING OF THE SITE IS R1 - RESIDENTIAL DISTRICT. THE ZONING IS TO REMAIN THE SAME. - FRONT = 40' - SIDE = 15' - REAR = 35'

6. THE SITE IS LOCATED WITHIN THE RESOURCE CONSERVATION AREA (RCA) OF THE CHESAPEAKE BAY

7. THE SITE IS CURRENTLY SERVED BY PRIVATE WELL AND SEPTIC.

8. THE TOPOGRAPHIC INFORMATION SHOWN ON THESE PLANS WAS DERIVED FROM A SURVEY PREPARED BY BAY ENGINEERING INC. IN APRIL, 2005. THE BOUNDARY SHOWN HEREON IS TAKEN FROM THE DEED AND RECORD PLAT (P.B. 19, PAGE 26). NO BOUNDARY SURVEY HAS BEEN PERFORMED BY BAY ENGINEERING INC.

9. THE ELEVATIONS OF THE FLOOD ZONE WERE OBTAINED FROM FEMA MAPS, PORTIONS OF THE SITE ARE LOCATED WITH A FEMA FLOOD ZONE "A6" (ELEV.= 7.0) AND "C" PER MAP #240008-0038C, PANEL 38 OF 61.

DRAWING INDEX

1 OF 3 COVER SHEET 2 OF 3 EXISTING SITE PLAN ADMINISTRATIVE VARIANCE SITE PLAN

VARIANCE REQUEST

THE APPLICANT IS REQUESTING A VARIANCE TO:

ARTICLE 27, TITLE 13, SECTION 104(A) OF THE ANNE ARUNDEL COUNTY CODE TO PERMIT A DWELLING AND ASSOCIATED FEATURES (I.E. WELL) WITHIN THE EXPANDED BUFFER

DEC 6 ZUUD

CRITICAL AREA COMMIS


gineering Inc. Bay Engineers, P Date NOVEMBER, 2005 Job Number 05-1562 Scale 1"=30" Drawn By L. SQUIRES Designed By T. SCHUMAN Approved By T. SCHUMAN Folder Reference YOUNG, ERIK CHILD'S POINT, BYWATER ESTATES


N R1/RCA SINGLE LOT GRADI


LOT

2 OF 3

B4-005 A







Date NOVEMBER, 2005 Job Number 05-1562 Drawn By L. SQUIRES Designed By T. SCHUMAN

Folder Reference YOUNG, ERIK CHILD'S POINT, BYWATER ESTATES

3 OF 3

B4-005 B

REVIEW THE APPROVED PLANS. (1 DAY) 2. INSTALL S.C.E. AND SILT FENCE AS SHOWN ON THE PLAN, PROTECT EXISTING UTILITIES. (5 DAYS)

DEMO EXISTING HOUSE AND PREPARE SITE FOR NEW HOUSE. (4 WEEKS)

4. EXCAVATE FOR & CONSTRUCT FOOTERS AND FOUNDATION, PRIOR TO FRAMING THE HOUSE, THE FOUNDATION MUST BE BACKFILLED AND SITE TEMPORARILY STABILIZED. MUST GET GRADING INSPECTOR'S APPROVAL

BEFORE CONTINUING. (3 WEEKS) 5. BEGIN HOUSE CONSTRUCTION AND EARTHWORK. (2 MONTHS)

RECONNECT UTILITIES, INSTALL SEPTIC (1 MONTH)

7. FINISH CONSTRUCTION OF HOUSE. (3 MONTHS) 8. FINE GRADE, FINAL PAVE WALKS AND DRIVE. (3 WEEKS)

9. PROVIDE SWM MITIGATION PLANTINGS PER SHEET 3. (2 WEEKS)

10. STABILIZE ALL DISTURBED AREAS WITH SEED AND MULCH AS SPECIFIED. WITH THE INSPECTORS

APPROVAL REMOVE ANY REMAINING SEDIMENT CONTROL DEVICES. (9 DAYS) 11. FINAL CLEAN UP BY DEVELOPER AND ONGING MAINTENANCE BY THE OWNERS

STANDARD RESPONSIBILITY NOTES

I (WE) CERTIFY THAT:

A. ALL DEVELOPMENT AND CONSTRUCTION WILL BE DONE IN ACCORDANCE WITH THIS SEDIMENT AND EROSION CONTROL PLAN, AND FURTHER, AUTHORIZE THE RIGHT OF ENTRY FOR PERIODIC ON-SITE: EVALUATION BY THE ANNE ARUNDEL SOIL CONSERVATION DISTRICT BOARD OF SUPERVISORS OR THEIR AUTHORIZED AGENTS.

B. ANY RESPONSIBLE PERSONNEL INVOLVED IN THE CONSTRUCTION PROJECT WILL HAVE A CERTIFICATE OF ATTENDANCE FROM THE MARYLAND DEPARTMENT OF THE ENVIRONMENT'S APPROVED TRAINING PROGRAM FOR THE CONTROL OF SEDIMENT AND EROSION BEFORE BEGINNING THE PROJECT.

RESPONSIBLE PERSON ON-SITE: TO BE DETERMINED

C. IF APPLICABLE, THE APPROPRIATE ENCLOSURE WILL BE CONSTRUCTED AND MAINTAINED ON SEDIMENT BASIN(S) INCLUDED IN THIS PLAN. SUCH STRUCTURE(S) WILL BE IN COMPLIANCE WITH THE ANNE ARUNDEL COUNTY CODE.

2. THE DEVELOPER IS RESPONSIBLE FOR THE ACQUISITION OF ALL EASEMENTS, RIGHT, AND/OR RIGHTS-OF-WAY THAT MAY BE REQUIRED FOR THE SEDIMENT AND EROSION CONTROL PRACTICES, STORMWATER MANAGEMENT PRACTICES AND THE DISCHARGE OF STORMWATER ONTO OR ACROSS ADJANCENT OR DOWNSTREAM PROPERTIES INCLUDED IN THE PLAN.

3. INITIAL SOIL DISTURBANCE OR REDISTURBANCE, PERMANENT STABILIZATION SHALL BE COMPLETED WITHIN SEVEN CALENDAR DAYS FOR THE SURFACE OF ALL CONTROLS, DIKES, SWALES, DITCHES, PERIMETER SLOPES, AND ALL SLOPES GREATER THAN 3 HORIZONTAL TO 1 VERTICAL (3:1) AND FOURTEEN DAYS FOR ALL OTHER DISTURBED OR GRADED AREAS ON THE PROJECT SITE. TEMPORARY STABILIZATION OF THE SURFACE OF PERIMETER CONTROLS, DIKES, SWALES, DITCHES, AND PERIMETER SLOPES MAY BE ALLOWED AT THE DISCRETION OF THE SEDIMENT CONTROL INSPECTOR.

4. THE SEDIMENT CONTROL APPROVALS ON THIS PLAN EXTEND ONLY TO AREAS AND PRACTICES IDENTIFIED AS PROPOSED WORK.

5. THE APPROVAL OF THIS PLAN FOR SEDIMENT AND EROSION CONTROL PLAN DOES NOT RELIEVE THE DEVELOPER/CONSULTANT FROM COMPLYING WITH ANY FEDERAL, STATE OR COUNTY REQUIREMENTS APPERTAINING TO ENVIRONMENTAL ISSUES.

6. THE DEVELOPER MUST REQUEST THAT THE SEDIMENT CONTROL INSPECTOR APPROVE WORK COMPLETED IN ACCORDANCE WITH THE APPROVED EROSION AND SEDIMENT CONTROL PLAN, THE GRADING OR BUILDING PERMIT, AND THE ORDINANCE.

7. ALL MATERIAL SHALL BE TAKEN TO A SITE WITH AN APPROVED SEDIMENT AND EROSION CONTROL PLAN.

8. ON ALL SITES WITH DISTURBED AREAS IN EXCESS OF 2 ACRES, APPROVAL OF THE SEDIMENT AND EROSION CONTROL INSPECTOR SHALL BE REQUIRED ON COMPLETION OF INSTALLATION OF PERIMETER EROSION AND SEDIMENT CONTROLS, BUT BEFORE PROCEEDING WITH ANY OTHER EARTH DISTURBANCE OR GRADING. OTHER BUILDING OR GRADING INSPECTION APPROVALS MAY NOT BE AUTHORIZED UNTIL THE INITIAL APPROVAL BY THE SEDIMENT AND EROSION CONTROL INSPECTOR IS GIVEN.

9. APPROVAL SHALL BE REQUESTED ON FINAL STABILIZATION OF ALL SITES WITH DISTURBED AREAS IN EXCESS OF 2 ACRES BEFORE REMOVAL OF CONTROLS.

10. EXISTING TOPOGRAPHY MUST BE FIELD VERIFIED BY RESPONSIBLE PERSONNEL TO THE SATISFACTION OF THE SEDIMENT CONTROL INSPECTOR PRIOR TO COMMENCING WORK.

SIGNATURE OF DEVELOPER/OWNER

DATE

NAME: ERIK B. YOUNG TITLE: OWNER

AFFILIATION: N/A ADDRESS: 15005 SHADY GROVE ROAD, SUITE 350, ROCKVILLE MD 20850 TELEPHONE NUMBER: 301-424-4803

CONSULTANT'S CERTIFICATION

"THE DEVELOPER'S PLAN TO CONTROL SILT AND EROSION IS ADEQUATE TO CONTAIN THE SILT AND EROSION ON THE PROPERTY COVERED BY THIS PLAN. I CERTIFY THAT THIS PLAN OF EROSION AND SEDIMENT CONTROL REPRESENTS A PRACTICAL AND WORKABLE PLAN BASED ON MY PERSONAL KNOWLEDGE OF THIS SITE, AND WAS PREPARED IN ACCORDANCE WITH THE REQUIREMENTS OF THE ANNE ARUNDEL SOIL CONSERVATION DISTRICT PLAN SUBMITTAL GUIDELINES AND THE CURRENT MARKETAND CONDARDS AND SPECIFICATIONS OF ZIMENT CONTROL PLAN WITH SEDIMENT AND EROSION CONTROL. I HAVE REVIEWED TH THE OWNER/DENELOPER."

BY:TERRY L. SCHUMAN, P.E

BAY ENGINEERING, INC. MARYLAND REGISTERED PROFESSIONAL ENGINEER # 19593

POST DEVELOPMENT OWNER/DEVELOPER'S STABILIZATION CERTIFICATION

"ALL GRADING DRAINAGE STRUCTURES AND/OR SYSTEMS, EROSION AND SEDIMENT CONTROL PRACTICES INCLUDING FACILITIES AND VEGETATIVE MEASURES HAVE BEEN COMPLETED IN CONFORMANCE WITH THE APPROVED PLANS AND SPECIFICATIONS".

OWNER/DEVELOPER

STORMWATER MANAGEMENT RECORD DRAWING CERTIFICATION


THIS CERTIFIES TO THE BEST OF MY PROFESSIONAL BELIEF AND KNOWLEDGE, THE APPROVED S.W.M. SYSTEM(S) AS SHOWN HEREON HAVE BEEN CONSTRUCTED IN SUCH A MANNER THAT WOULD BE CONSISTENT WITH THE APPROVED PLANS. ANY CHANGES/MODIFICATIONS ARE IDENTIFIED IN RED.

TIMOTHY J. MARTIN, L.S.# 10989


LEGEND

PROPERTY LINE / RIGHT-OF-WAY EXISTING CONTOUR 142 -----EXISTING SPOT ELEVATION 30.50 MYMY EXISTING WOODS LINE EXISTING TREE / TREE TO BE REMOVED EXISTING ZONING DESIGNATION EXISTING UTILITY POLE W/ OVERHEAD WIRE **EXISTING FENCE** EXISTING SEWER EXISTING 15% TO 25% SLOPES **EXISTING SLOPE GREATER THAN 25%** 25' STEEP SLOPE BUFFER EXISTING 100' BUFFER TO MHW

EXPANDED CRITICAL AREA BUFFER



FEMA FLOOD ZONE BOUNDARY



OVERALL SITE AREA MAP

SCALE: 1"=200' TOPO: A.A.Co., D.P.W.

OUTFALL STATEMENT

A FIELD INVESTIGATION OF THE OUTFALL AND THE CONVEYANCE SYSTEM DOWNSTREAM WAS PERFORMED ON SEPTEMBER 23, 2005 BY BAY ENGINEERING, INC. THE PROJECT CURRENTLY DISCHARGES THROUGH OVERLAND FLOW ACROSS THE EXISTING SLOPES TO THE WATER. DEVELOPMENT OF THE SITE WILL REDUCE THE TOTAL IMPERVIOUS SURFACE ON THE SITE.

VARIANCE STATEMENT

THE APPLICANT HAS RECEIVED APPROVAL OF A VARIANCE TO DISTURB AREAS WITHIN THE EXPANDED BUFFER AND A VARIANCE TO DISTURBANCE OF SLOPES OF 15% OR GREATER. CASE # 2005-0297-V. APPROVED ON DECEMBER 21, 2005. SUBJECT TO THE FOLLOWING CONDITIONS:

1. NO FURTHER EXPANSION OF THE DWELLING IS ALLOWED. 2. THE BUILDING PERMIT IS SUBJECT TO THE APPROVAL OF THE DEPARTMENT OF HEALTH. 3. THE APPLICANT SHALL PROVIDE MITIGATION AT A 3:1 RATE

WITH PLANTINGS OF NATIVE SPECIES ON-SITE.

BENCHMARK INFORMATION

BENCHMARK #311 (A.A. CO. MONUMENT) - BEING A CONCRETE MONUMENT SET AT THE INTERSECTION OF FOREST DRIVE AND SPA ROAD: N 472923-270 E 1450835.533 ELEV. = 52.234 VERTICAL CONTROL: 1929 NGVD HORIZONTAL CONTROL: NAD 83 DATUM

PERMIT INFORMATION

GRADING PERMIT #: G02 **BUILDING PERMIT #:B02** VARIANCE CASE #: 2005-0297-\ PERC. APPLICATION #: T02033599

DRAWING INDEX 1 OF 5


2 OF 5

3 OF 5

4 OF 5

5 OF 5

...COVER SHEET . EXISTING CONDITIONS AND DEMOLITION PLAN . SITE, GRADING, AND SEDIMENT CONTROL PLAN DETAILS AND NOTES SEPTIC SITE PLAN



SCALE: 1" = 2000' COPYRIGHT ADC THE MAP PEOPLE PERMITTED USE NO. 20400770

PURPOSE STATEMENT: THE PURPOSE OF THESE PLANS IS TO REFLECT THE EXISTING AND PROPOSED SITE CONDITIONS FOR REPLACING A SINGLE FAMILY HOME ON LOT 9, 'BYWATER ESTATES'.

ALL SITE WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST EDITIONS OF THE ANNE ARUNDEL COUNTY DEPARTMENT OF PUBLIC WORKS REQUIREMENTS AND SPECIFICATIONS UNLESS OTHERWISE DETAILED OR SPECIFIED

THE EXISTING UTILITIES AND OBSTRUCTIONS SHOWN ARE FROM THE BEST AVAILABLE RECORDS AND SHALL BE FIELD VERIFIED BY THE CONTRACTOR TO HIS OWN SATISFACTION PRIOR TO ANY CONSTRUCTION. ANY UTILITIES DAMAGED

DUE TO THE CONTRACTOR'S NEGLIGENCE SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR'S EXPENSE. 3.) THE CONTRACTOR SHALL CALL "MISS UTILITY" (1-800-257-7777) A MINIMUM OF 5 DAYS IN ADVANCE OF ANY CONSTRUCTION AND /OR EXCAVATION.

GENERAL NOTES

4.) THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING ANY FENCE, DRIVEWAY, LANDSCAPING, ETC. DAMAGED OR REMOVED BY HIM DURING CONSTRUCTION. ALL DISTURBED AREAS OUTSIDE THE RIGHT OF WAY LINES SHALL BE RETURNED TO THEIR ORIGINAL CONDITION UNLESS OTHERWISE INDICATED AND SPECIFIED.

IT SHALL BE DISTINCTLY UNDERSTOOD THAT FAILURE TO MENTION SPECIFICALLY ANY WORK THAT WOULD NATURALLY BE REQUIRED TO COMPLETE THE PROJECT SHALL NOT RELIEVE THE CONTRACTOR OF HIS RESPONSIBILITY TO PERFORM SUCH WORK.

THESE DRAWINGS DO NOT INCLUDE THE NECESSARY COMPONENTS FOR CONSTRUCTION SAFETY. ALL CONSTRUCTION MUST BE DONE IN COMPLIANCE WITH THE LATEST VERSION OF OSHA STANDARDS AND/OR

IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY THE ENGINEER OF ANY DEVIATION TO THIS PLAN PRIOR TO ANY CHANGE BEING MADE. ANY CHANGE IN THIS PLAN MADE WITHOUT THE WRITTEN AUTHORIZATION FOR SAID CHANGE FROM THE ENGINEER SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR OR THE SUBCONTRACTOR. SAIDCHANGES MAY WARRANT COUNTY REVIEW AND APPROVAL.

8.) THE CONTRACTOR SHALL NOTE THAT IN THE CASE OF A DISCREPANCY BETWEEN THE SCALED AND THE FIGURED DIMENSIONS SHOWN ON THESE PLANS, THE FIGURED DIMENSION SHALL GOVERN.

9.) THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION OF HIS CONSTRUCTION WITH THE CONSTRUCTION BY OTHER CONTRACTORS, SUBCONTRACTORS.

10.) IF NECESSARY, ALL UTILITY POLES SHALL BE BRACED WHEN NECESSARY AT THE CONTRACTORS EXPENSE. THE UTILITY POLES SHALL BE RELOCATED AT THE OWNER'S EXPENSE ONLY IN CASES WHERE THEY WILL INTERFERE WITH

11.) ALL AVAILABLE UTILITIES (IE., ELECTRIC, WATER, GAS, AND COMMUNICATIONS) SHALL BE PROVIDED FROM EXISTING ADJACENT FACILITIES AND IN ACCORDANCE WITH THE UTILITY COMPANY REQUIREMENTS.

12.) THE CONTRACTOR IS CAUTIONED THAT UNDERGROUND CABLES MAY EXIST IN THE PUBLIC RIGHT OF WAY AND BEYOND. WORK IN AND OUT OF THE RIGHT OF WAY SHOULD NOT BEGIN UNTIL THE CONTRACTOR IS FAMILIAR WITH THE LOCATION AND DEPTH OF CABLES. ANY DAMAGE TO EXISTING UTILITY SERVICES SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR COST.

13.) JOB SAFETY IS THE SOLE THE RESPONSIBILITY OF THE CONTRACTOR, SUBCONTRACTORS AND VENDORS.

14.) THE SITE IS SERVED BY PRIVATE WELL AND PRIVATE SEPTIC. THE CONTRACTOR SHALL VERIFY THE LOCATION OF THE EXISTING SERVICES, FILE RE-CONNECTION APPLICATIONS AND PERFORM CONNECTIONS.

15.) ALL STRUCTURAL FILL SHALL BE PLACED IN 8" LOOSE LAYERS AND COMPACTED TO 95% MAXIMUM DRY DENSITY AT OPTIMUM MOISTURE CONTENT AS DETERMINED BY AASHTO T-180 METHOD, THE CONTRACTOR SHALL USE CLASS SELECT MATERIALS FOR THE FOOTINGS FOUNDATIONS AND BACK FILL FOR ALL FOUNDATION AND RETAINING WALLS.

16.) THE TOPOGRAPHIC INFORMATION SHOWN ON THE SITE PLAN WAS DERIVED FROM SURVEY PREPARED BY BAY ENGINEERING, INC., APRIL, 2005.

17.) THE ELEVATIONS OF THE FLOOD ZONE WERE OBTAINED FROM FEMA MAPS, PORTIONS OF THIS SITE ARE LOCATED WITHIN A FEMA FLOOD ZONE A6 (ELE 7) AND C, MAP #240008 0038 D, PANEL 38 OF 61.

18.) THE UNITED STATES DEPARTMENT OF AGRICULTURE SOIL SURVEY REVIEWED ON FILE WITH ANNE ARUNDEL COUNTY SOIL CONSERVATION DISTRICT INDICATED THAT THE MAJOR SOIL CLASSIFICATION IS MVE, MONMOUTH FINE SANDY LOAM AS PER MAP 27 OF SOIL SURVEY OF A.A.CO., MD.

19.) ALL ROOF DRAINS SHALL BE DISCHARGED ONTO SPLASH BLOCKS.

TOTAL BORROW TO BE BROUGHT TO THE SITE IS 0 CUBIC YARDS.

20.) ZONING IS R1. YARDS AND SETBACKS: FRONT 30, SIDE 7/20 COMBINED, REAR 25.

21.) SITE PLAN TABULATIONS: TOTAL SITE AREA: 188,307 SF OR 4.323 ACRES TOTAL DISTURBED AREA: 13,125 SF OR 0.3 ACRES (EXCLUDES EX. DRIVEWAY) EXISTING IMPERVIOUS COVERAGE IS 12,898 SF OR 0.296 ACRES (6.9%) PROPOSED IMPERVIOUS COVERAGE: 12,244 SF OR 0.28 ACRES (6.5%) IMPERVIOUS COVERAGE PERMITTED IS 15 % OR 28,246 SF TOTAL AREA VEGETATIVELY STABILIZED IS 881 SF OR 0.02 ACRES. TOTAL AREA STRUCTURALLY STABILIZED IS 12,244 SF OR 0.26 ACRES. TOTAL CUT ON SITE IS 475 CUBIC YARDS. TOTAL FILL ON SITE IS 475 CUBIC YARDS. TOTAL SPOIL TO BE PLACED ONSITE IS 0 CUBIC YARDS.

22.) NO BOUNDARY SURVEY WAS PERFORMED BY BAY ENGINEERING, INC. AT THIS TIME. THIS PLAN WAS PREPARED WITHOUT BENEFIT OF A TITLE REPORT, WHICH MAY SHOW ADDITIONAL CONVEYANCES, EASEMENTS, COVENANTS, RIGHT OF WAYS OR MORE STRINGENT BUILDING RESTRICTIONS NOT SHOWN HEREON. PROPERTY OUTLINES SHOWN HEREON TAKEN FROM RECORDED DEED 16301 / 199.

23.) THE SITE IS MAPPED NON-BUFFER EXEMPT AS MAP 51 OF CRITICAL AREA OVERLAY.

24.) THE SITE IS LOCATED WITHIN THE LIMITED DEVELOPMENT AREA (LDA) OF THE CHESAPEAKE BAY CRITICAL AREA.


25.) PROPERTY TAX ID: 02-145-01867400. TAX MAP 51, GRID 21, PARCEL 169, LOT 9 OF BYWATER ESTATES SUBDIVISION RECORDED IN PLAT 19 / 26.

THIS SITE IS NOT WITHIN THE SEVERN RIVER WATERSHED

Anne Arundel Soil Conservation District Sediment and Erosion Control Approva

AASCD# 6 18- 29 SMALL POND (S)# NHA

Reviewed for technical adequacy by USDA, Natural Resources Conservation Service



Bay

AUGUST, 2006 **Job Number** 05-1562 Scale AS SHOWN Drawn By

L.K.C. Designed By G.M.E. **Approved By**

J.E.S. YOUNG ERIK CHILD POINT

BYWATER

0

1 OF 5


05-1562


GENERAL DEMOLITION NOTES

- ALL DEMOLITION ACTIVITIES ARE TO BE PERFORMED IN STRICT ADHERENCE TO ALL FEDERAL, STATE AND LOCAL REGULATIONS.
- PROCEED WITH DEMOLITION IN A SYSTEMATIC MANNER, FROM THE
- TOP OF THE STRUCTURE(S) TO THE GROUND. COMPLETE DEMOLITION WORK ABOVE EACH FLOOR OR TIER
- BEFORE DISTURBING ANY OF THE SUPPORTING MEMBERS OF THE LOWER LEVELS.
- DEMOLISH CONCRETE AND MASONRY IN SMALL SECTIONS.
- REMOVE STRUCTURAL FRAMING MEMBERS AND LOWER THEM TO THE GROUND BY MEANS OF HOISTS, DERRICKS OR OTHER SUITABLE
- BREAK UP CONCRETE SLABS-ON-GRADE, UNLESS OTHERWISE DIRECTED BY THE CLIENT.
- LOCATE DEMOLITION EQUIPMENT THROUGHOUT THE STRUCTURE AND REMOVE MATERIALS SO AS TO NOT IMPOSE EXCESSIVE LOADS ON SUPPORTING WALLS, FLOORS, OR FRAMING.
- PROVIDE INTERIOR AND EXTERIOR SHORING, BRACING AND SUPPORTS TO PREVENT MOVEMENT, SETTLEMENT OR COLLAPSE OF STRUCTURES TO BE DEMOLISHED (AND ADJACENT FACILITIES, IF APPLICABLE).

25' BUFFER TO

- DEMOLISH AND REMOVE FOUNDATION WALLS, FOOTING AND OTHER MATERIALS WITHIN THE AREA OF THE DESIGNATED FUTURE BUILDING. ALL OTHER FOUNDATION SYSTEMS, IF ANY, SHALL BE DEMOLISHED TO A DEPTH OF NOT LESS THEN ONE FOOT BELOW PROPOSED PAVEMENT GRADE. BREAK BASEMENT FLOOR SLABS. SEAL ALL OPEN UTILITY LINES WITH CONCRETE.
- CONDUCT DEMOLITION SERVICES IN SUCH A MANNER TO ENSURE MINIMUM INTERFERENCE WITH ROADS, STREETS, WALKS AND OTHER ADJACENT FACILITIES. DO NOT CLOSE OR OBSTRUCT STREETS, WALKS AND OTHER OCCUPIED FACILITIES WITHOUT PRIOR WRITTEN PERMISSION OF THE CLIENT AND ANY APPLICABLE GOVERNMENTAL AUTHORITIES. PROVIDE ALTERNATE ROUTES AROUND CLOSED OR OBSTRUCTED TRAFFIC WAYS, IF REQUIRED BY APPLICABLE GOVERNMENTAL REGULATION.
- USE WATERING, TEMPORARY ENCLOSURES AND OTHER SUITABLE METHODS, AS NECESSARY TO LIMIT THE AMOUNT OF DUST AND DIRT RISING AND SCATTERING IN THE AIR. CLEAN ADJACENT STRUCTURES AND IMPROVEMENTS OF ALL DUST AND DEBRIS CAUSED BY THE DEMOLITION OPERATIONS. RETURN ALL ADJACENT AREAS TO THE CONDITIONS EXISTING PRIOR TO THE START OF WORK.
- 12. ACCOMPLISH AND PERFORM THE DEMOLITION IN SUCH A MANNER AS TO PREVENT THE UNAUTHORIZED ENTRY OF PERSONS AT ANY
- 13. COMPLETELY FILL BELOW GRADE AREAS AND VOIDS RESULTING FROM THE DEMOLITION OF STRUCTURES AND FOUNDATIONS WITH SOIL MATERIALS CONSISTING OF STONE, GRAVEL, AND SAND, FREE FROM DEBRIS, TRASH, FROZEN MATERIALS, ROOTS AND OTHER ORGANIC MATTER. STONES USED WILL NOT BE LARGER THAN 6 INCHES IN DIMENSION. MATERIAL FROM DEMOLITION MAY NOT BE USED AS FILL, PRIOR TO PLACEMENT OF FILL MATERIALS. UNDERTAKE ALL NECESSARY ACTION IN ORDER TO INSURE THAT AREAS TO BE FILLED ARE FREE OF STANDING WATER, FROST, AND FROZEN MATERIAL, TRASH DEBRIS, PLACE FILL MATERIALS IN HORIZONTAL LAYERS NOT EXCEEDING 6 INCHES IN LOOSE DEPTH AND COMPACT EACH LAYER AT PLACEMENT TO 95% OPTIMUM DENSITY. GRADE THE SURFACE TO MEET ADJACENT CONTOURS AND TO PROVIDE SURFACE DRAINAGE.
- 14. REMOVE FROM THE DESIGNATED SITE, AT THE EARLIEST POSSIBLE TIME, ALL DEBRIS, RUBBISH, SALVAGEABLE ITEMS, HAZARDOUS AND COMBUSTIBLE SERVICES. REMOVE MATERIALS MAY NOT BE STORED, SOLD OR BURNED ON THE SITE. REMOVAL OF HAZARDOUS AND COMBUSTIBLE MATERIALS SHALL BE ACCOMPLISHED IN ACCORDANCE WITH THE PROCEDURES AS AUTHORIZED BY THE FIRE DEPARTMENT OR OTHER APPROPRIATE REGULATORY AGENCIES AND AUTHORITIES.
- DISCONNECT, SHUT OFF AND SEAL IN CONCRETE ALL UTILITIES SERVING THE STRUCTURE(S) TO BE DEMOLISHED BEFORE THE COMMENCEMENT OF THE DESIGNATED DEMOLITION. MARK FOR POSITION ALL UTILITY DRAINAGE AND. SANITARY LINES AND PROTECT ALL ACTIVE LINES, CLEARLY IDENTIFY, BEFORE THE COMMENCEMENT OF DEMOLITION, SERVICES THAT REQUIRE INTERRUPTION OF ACTIVE SYSTEMS THAT MAY AFFECT OTHER PARTIES, AND NOTIFY ALL APPLICABLE UTILITY COMPANIES TO INSURE THE CONTINUATION OF SERVICE.
- 16. PRIOR TO THE ONSET OF DEMOLITION, THE CONTRACTOR SHALL LOCATE ALL EXISTING UTILITIES ON SITE AND COORDINATE REMOVAL OF SAID UTILITIES WITH THE RESPECTIVE UTILITY
- 17. PRIOR TO THE ONSET OF DEMOLITION THE CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AS REQUIRED BY LOCAL AGENCIES, THE STATE OF MARYLAND AND ANY APPLICABLE FEDERAL AGENCIES.
- 18. ANY OTHER FEATURE NOT SHOWN ON THIS SURVEY, BUT NOT SITE SPECIFIC TO THE CLIENT ARE TO BE REMOVED, INCLUDING BUT NOT LIMITED TO LIGHT POLES, FENCES, AND SIGNS.
- 19. THE CONTRACTOR IS RESPONSIBLE FOR SAFETY ON THE SITE AT ALL TIMES DURING THE DEMOLITION PROCESS.
- 20. LOCATION OF ALL UNDERGROUND UTILITIES ARE APPROXIMATE, ALL LOCATIONS ARE SIZED ARE BASED ON UTILITY MARK-OUTS, ABOVE GROUND STRUCTURES THAT WERE VISIBLE AND ACCESSIBLE IN THE FIELD, AND THE MAPS AS LISTED IN THE REFERENCES AVAILABLE AT THE TIME OF THE SURVEY. AVAILABLE AS-BUILTS PLANS AND UTILITY MARKOUTS DO NOT ENSURE MAPPING OF ALL UNDERGROUND UTILITIES AND STRUCTURES. BEFORE ANY EXCAVATION IS TO BEGIN, ALL UNDERGROUND UTILITIES SHOULD BE VERIFIED AS TO THEIR LOCATION, SIZE AND TYPE BY THE PROPER UTILITY COMPANY.
- 21. ALL CONSTRUCTION ACTIVITIES SHALL TAKE PLACE IN A MANNER TO REASONABLY MINIMIZE DISTURBANCE TO ADJOINING





lic, ngineering

AUGUST, 2006 05-1562 Scale AS SHOWN Drawn By L.K.C. **Designed By** T.L.S.


Approved By T.L.S. **Folder Reference**


YOUNG ERIK CHILD POINT


BYWATER

9

2 OF 5 05-1562







Ingineering Inc.

Date AUGUST, 2006 **Job Number** 05-1562

Scale AS SHOWN Drawn By L.K.C.

Folder Reference

YOUNG ERIK CHILD POINT

c 0

3 OF 5 05-1562

A. Soil Tests: Lime and fertilizer will be applied per soil tests results for sites greater than 5 acres. Soil tests will be done at completion of initial rough grading or as recommended by the sediment control inspector. Rates and analyses will be provided to the grading inspector as well as the contractor.

1. Occurrence of acid sulfate soils (grayish black color) will require covering with a minimum of 12 inches of clean soil with 6 inches minimum capping of top soil. No stockpiling of material is allowed. If needed, soil tests should be done before and after a 6-week incubation period to allow oxidation of sulfates.

The Minimum soil conditions required for permanent vegetative establishment are: a. Soil pH shall be between 6.0 and 7.0

b. Soluble salts shall be less than 500 parts per million (ppm). c. The soil shall contain less than 40% clay but enough fine-grained material (> 30% silt plus clay) to provide the capacity to hold a moderate amount of moisture. An exception is if lovegrass or serecia lespedeza is to be planted, then a sandy soil (< 30% silt plus clay) would be acceptable.

d. Soil shall contain 1.5% minimum organic matter by weight.

fourteen days for all other disturbed or graded areas on the project site.

e. Soil must contain sufficient pore space to permit adequate root penetration. f. If these conditions cannot be met by soils on site, adding topsoil is required in accordance with Section 21 Standard and Specification for Topsoil or amendments made as recommended by a certified agronomist.

B. Seedbed Preparation: Area to be seeded shall be loose and friable to a depth of at least 3 inches. The top layer shall be loosened by raking, disking or other acceptable means before seeding occurs. For sites less than 5 acres, apply 100 pounds dolomitic limestone and 21 pounds of 10-10-10 fertilizers per 1,000 square feet. Harrow or disk lime and fertilizer into the soil to a depth of at least 3 inches on slopes flatter than 3:1.

C. Seeding: Apply 5-6 pounds per 1,000 square feet of tall fescue between February 1 and April 30 or between August 15 and October 31. Apply seed uniformly on a mist firm seedbed with a cyclone seeder, cultipacker seeder or hydroseeder (slurry includes seeds and fertilizer recommended on steep slopes only). Maximum seed depth should be 1/4 inch in clayey soils and 1/2 inch sandy soils when using other than the hydroseeder method. Irrigate where necessary to support adequate growth until vegetation is firmly established. If other mixes are to be used, select from Table 25, entitled "Permanent Seeding For Low Maintenance Areas" from the current Standards and Specifications for Soil Erosion and Sediment Control. Mixes suitable for this are 1, 3 and 5-7. Mixes 5-7 are suitable in non-mowable situations.

D. Mulching: Mulch shall be applied to all seeded areas immediately after seeding. During the time periods when seeding is not permitted, mulch shall be applied immediately after grading.

Mulch shall be unrotted; unchopped, small grain straw applied at a rate of 2 tons per acre or 90 pounds per 1,000 square feet (2 bales). If a mulch-anchoring tool is used, apply 2.5 tons per acre. Mulch materials shall be relatively free of all kinds of weeds and shall be completely free of prohibited noxious weeds. Spread mulch uniformly, mechanically or by hand, to a depth of 1-2 inches.

E. Securing Straw Mulch: Straw mulch shall be secured immediately following mulch application to minimize movement by wind or water. The following methods are permitted:

(i) Use a mulch-anchoring tool, which is designed to punch and anchor mulch into the soil surface to a minimum depth of 2 inches. This is the most effective method for securing mulch, however, it is limited to relatively flat areas where equipment can operate safely.

(ii) Wood cellulose fiber may be used for anchoring straw. Apply the fiber binder at a net dry weight of 750 pounds per acre. If mixed with water, use 50 pounds of wood cellulose fiber per

(iii) Liquid binders may be used. Apply at higher rates at the edges where wind catches mulch, such as in valleys and in crests of slopes. The remainder of the area should appear uniform after binder application. Binders listed in the 1994 Standards and Specifications for Soil Erosion and Sediment Control or approved equal shall be applied at rates recommended by

(iv) Lightweight plastic netting may be used to secure mulch. The netting will be stapled to the ground according to manufacturer's recommendations.

2. Temporary Seeding:

Lime: 100 Pounds of dolomitic limestone per 1,000 square feet.

Fertilizer: 15 pounds of 10-10-10 per 1,000 square feet.

Seed: Perennial rye-0.92 pounds per 1,000 square feet (February 1 through April 30 or August 15 through November 1).

Millet-0.92 pounds per 1,000 square feet (May 1 through August 15)

Mulch: Same as 1 D and E. above.

3. No fills may be placed on frozen ground. All fill to be placed in approximately horizontal layers, each layer having a loose thickness of not more than 8 inches. All fill in roadways and parking areas is to be classified Type 2 as per Anne Arundel County Code -Article 21, Section 2-308, and compacted to 90% density; compaction to be determined by ASTMD-1557-66T) (Modified Proctor). Any fill within the building area is to be compacted to a minimum of 95% density as determined by methods previously mentioned. Fills for pond embankments shall be compacted as per MD-378 Construction Specifications. All other fills shall be compacted sufficiently so as to be stable and prevent erosion and slippage.

4. Permanent Sod:

Installation of sod should follow permanent seeding dates. Seedbed preparation for sod shall be as noted in section (B) above. Permanent sod is to be tall fescue, state approved sod; lime and fertilizer per permanent seeding specifications and lightly irrigate soil prior to laying sod. Sod is to be laid on the contour with all ends tightly abutting. Joints are to be staggered between rows. Water and roll or tamp sod to insure positive root contact with soil. All slopes steeper than 3:1, as shown, are to be permanently sodded or protected with approved erosion control netting. Additional watering for establishment may be required. Sod is not to be installed on frozen ground. Sod shall not be transplanted when moisture content (dry or wet) and/or extreme temperature may adversely affect its survival. In the absence of adequate rainfall, irrigation should be performed to ensure establishment of sod.

Sediment control plans for mining operations must include the following seeding dates and

For seeding dates of:

UNDER 15% (6.5%).

February 1 through April 30 and August 15 through October 31, use seed mixture of tall fescue at the rate of 2 pounds per 1,000 square feet and sericea lespedeza at the minimum rate of 0.5 pounds per 1,000 square feet.

6. Topsoil shall be applied as per the Standard and Specifications for Topsoil from the current Maryland Standards and Specifications for Soil Erosion and Sediment Control.

NOTE: Use of this information does not preclude meeting all of the requirements of the current Maryland Standards and Specifications for Soil Erosion and Sediment Control.

NOTE: Projects within 4 miles of the BWI Airport will need to adhere to Maryland Aviation Administration's seeding specification restrictions.

S.W.M. COMPLIANCE NOTE

IN ACCORDANCE WITH ARTICLE 16, TITLE 3 OF THE COUNTY CODE THE DEVELOPMENT OF THIS LOT MUST COMPLY WITH THE QUALITATIVE AND QUANTITIVE STORMWATER MANAGEMENT CRITERIA CONTAINED IN THE STORMWATER MANAGEMENT PRACTICES AND PROCEDURES

THE FOLLOWING WILL SERVE AS THE RESIDENTIAL WATER QUALITY MANAGEMENT PLAN. THE WATER QUALITY FEATURES PROVIDED FOR THE RESIDENTIAL HOUSE AND DRIVEWAY CONSTRUCTION ARE AS FOLLOWS:

- ALL DECKS SHALL BE CONSTRUCTED WITH SPACES BETWEEN FLOOR BOARDS AND 6" OF GRAVEL BED FOR STABILIZATION PLACED UNDER DECK AND VEGETATIVE STABILIZATION @ BORDERS OF DECK.

- ALL ROOF DRAINAGE FOR THE MAIN HOUSE SHALL BE DISCONNECTED TO DIRECT RUNOFF TO A STABLE GRASS AREA. - CREDITS: THE SITE QUALIFIES FOR THE SENSITIVE DEVELOPMENT CREDIT AS THE TOTAL SITE

AREA IS GREATER THAN 2 ACRES (4.3 ACRES) AND THE SITE IMPERVIOUS PERCENTAGE IS

CONSTRUCTION NOTES:

1. All graded and disturbed areas including slopes shall be protected during clearing and construction in accordance with the approved erosion and sediment control plan until they are adequately stabilized.

2. All erosion and sediment control practices and measures shall be constructed, applied and maintained in accordance with the approved sectiment control plan and all applicable Local, State, and Federal Standards and Specifications for Soil Erosion and Sediment Control.

3. Topsoil required for the establishment of vegetation shall be stockpiled in the amount necessary to complete finished grading of all exposed areas.

4. Areas to be filled shall be cleared, grubbed and stripped of topsoil, remove trees, vegetation, roots or other

5. Areas which are to be top soiled shall be scarified to a minimum depth of three (3) inches prior to placement of

6. All fills shall be compacted to 95% maximum density ASTM D-1557 (AASHTO T-180) Method-C at optimum moisture as required to reduce ercsion, slippage, settlement, subsidence or other related problems. Fill intended to support buildings, structures and conduits, etc. shall be compacted in accordance with above stated or local requirements and codes, whichever are more stringent.

7. All fill shall be placed and compacted in layers not to exceed eight inches (8") in thickness.

8. Except for approved landfills or nonstructural fills, fill material shall be free of brush, rubbish, rocks, logs stumps, building debris and other objectionable materials that would interfere with, or prevent, construction of satisfactory

9. Frozen materials or soft, mucky or highly compressible materials shall not be incorporated into fill slopes or structural fills. Fill shall not be placed on a frozen foundation.


10. Groundwater, Seeps or springs encountered during construction shall be handled in accordance with the local Building Code, Standards and Specifications for Subsurface Drain or other approved methods. If conditions are staturated employ a design professional for foundation design and construction inspections. Require a final certification after foundation cure period and prior to first floor decking is placed.

11. Stockpiles, borrow areas, and spoil areas shall be shown on the plans and shall be subject to the provisions of all applicable local, state, and federal Standard and Specifications.

12. Grade all disturbed areas with positive drainage at 2% (percent) slope minimum.


13. Footers for building or house construction to be in virgin soil or on compacted soils designed and specified by a

14. Trees shall not be removed from building pad locations unless approval for building pad grading has been acquired or until such time as Grading plans for each lot are completed, submitted, and approved with each





DRIVEWAY PAVING SECTION

OR APPROVED EQUAL FOR MATERIALS AND DEPTH NOTE: OWNER RESERVES THE RIGHT TO CHANGE THE PAVING SECTION TO A GRAVEL SECTION



EVERGREEN TREE PLANTING DETAIL






TREE PLANTING DETAIL


REFORESTATION PLANT L'ST:

Plant List:					
SYMBOL	QTY	COMMON NAME	BOTANICAL NAME	HEIGHT	SIZE
0	46 OGM 2-1/2 cal.	Maple, October Glory	Acer Rubrum	6'	1 1/2" Caliper
•	138 SB Cont. 6'-16'	Spicebush	Lindera benzoin		3-4 Gallon

Plant materials may be changed in accordance with native materials listed as approved by Anne Arundel County, locations may be changed in the field to suit conditions.




TREE GUYING PLAN



DETAIL 24 - STABILIZED CONSTRUCTION ENTRANCE

THERE ARE NO WELL



OFF-SITE MITIGATION FEE ...

(3:1 FOR DISTURBED AREA WITHIN THE EXPANDED BUFFER AND

THERE ARE NO WELL

Siit Fence Design Criteria Slepe Steepness Slit Fence Length Slope Length Flatter than 50: unlimited 125 feet 1,000 feet 50:1 to 10: 10:1 to 5:1 60 feet 500 feet 5:1 to 3:1 3:1 to 2:1 40 foet 250 feet MINIMUM 2D" ABOVE GROUND 2:1 and steeper Note; In areas of less than 2% slope and sandy soils (USDA general classification system, soll Class A) maximum slope length and slit fence length will be unlimited. In these areas a slit fence may be the only perimeter control INIMUM OF 16° INTO
 Tensile Strength
 50 lbs/in (min.)
 Test: MSMT 509

 Tensile Modulus
 20 lbs/in (min.)
 Test: MSMT 509

 Flow Rato
 0.3 gal ft / minute (max.)
 Test: MSMT 322
 Test: MSMT 322 4. Silt Fence shall be inspected after each rainfall event and maintained whe rulges occur or when sediment accumulation reached 50% of the fabric height.

gineering AUGUST, 2006 05-1562 Scale AS SHOWN Drawn By **Designed By**

CRITICAL AREA REFORESTATION MITIGATION SUMMARY (NEW DEVELOPMENT)

W/IN EXPANDED BUFFER	OUTSIDE EXPANDED BUFFER	TOTAL
5,916 SQ. FT. ± 17,748 SQ. FT. ±	7,209 SQ. FT. ± 565 SQ. FT. ±	13,125 SQ. FT. ± 18,313 SQ. FT. ±
	W/IN EXPANDED BUFFER 5,916 SQ. FT. ±	BUFFER BUFFER 5,916 SQ. FT. ± 7,209 SQ. FT. ±

SILT FENCE

1:1 FOR MITIGATION OF FOREST CLEARED OUTSIDE BUFFER)

THE PROPOSED WOODLAND CLEARED OUTSIDE THE EXPANDED BUFFER IS 5 TREES (12" DBH) WHICH EQUATES TO A TREE CANOPY OF APPROXIMATELY 565 SQ. FT. OF FOREST

ON-SITE MITIGATION AREA TO BE PLANTED ON-SITE (REQUIREMENT 1 TREE & 3 SHRUBS PER 400 SQ. FT.) PROPOSED TREES (1 TREE PER 250 SQ. FT.)..... PROPOSED SHRUBS (1 SHRUB PER 50 SQ. FT.).... TOTAL MITIGATION BOND AMOUNT (\$1.20 / SQ. FT.) .. (\$1.20 x 18,313 SQ. FT.) TOTAL NEW SECURITY

18,313 SQ. FT. ± 46 TREES 138 SHRUBS 18,313 SQ. FT. Approved By \$21,975.60 Folder Reference \$21,975.60 CHILD POINT

BYW

တ

Sheet No. File No. 05-1562

Frances B. Phillips Health Officer

March 18, 2005

MARC TEREN 432 NEW JERSEY AVE. SE. WASHINGTON, DC 20003

RE: Perc #T02033599 Tax Account #214501867400 Site: 870 CHILDS POINT ROAD **ANNAPOLIS**

The Anne Arundel County Department of Health has completed an evaluation of the above referenced property. Percolation test(s) were conducted on March 1, 2005 at the above site. Based on the tests conducted the proposed initial septic system and replacements must consist of:

Septic Tank 1500 gallon

Initial Drywell/Seepage Pit:

Replacement systems:

Total Depth 32 feet Diameter 8 feet No. of Pits 3

Total Depth feet Diameter feet

Pits Separated by 24 feet from edge to edge

No. of Pits Pits Separated by feet from edge to edge

Other: SHOW DRYWELLS IN AREA OF TEST 5, SHOW A 3600 SQ. FOOT MOUND IN AREA OF TESTS 1&4.SHOW 1' TOPO IN MOUND AREA.SHOW SYSTEM 25' FROM 25% SLOPE.EXISTING DUG WELL MUST BE ABANDONED. AN APPROVED NITROGEN REDUCING UNIT IS REQUIRED DUE TO CRITICAL AREA, NO VARIANCES TO SIZING OR REPLACEMENTS WILL BE ALLOWED

The above recommendations are for a house larger than 3500 square feet and does not constitute Health Department approval of the site.

Before approval of a septic system for this property is considered, eight (8) copies of a scaled site plan including the layout of the proposed initial septic system and 2 replacement(s) must be submitted containing the information listed on the Site Plan Information Sheet attached.

> Anne Arundel County Department of Health Division of Environmental Health • 3 Harry S. Truman Parkway • Annapolis, MD 21401 Phone 410-222-7193 • Fax 410-222-7294 • www.aahealth.org

The following table is a compilation of pre and post development condition data as determined using TR-55.

Drainage Area 1A	Pre	Post
Site Area (Ac.)	4.32	4.32
Drainage Area (Ac.)	1.28	1.28
CN	73	73
T _c (Hours)	0.13	0.07
Q _{p 10 year} (cfs)	4.5	4.7

Drainage Area 1B	Pre	Post
Site Area (Ac.)	4.32	4.32
Drainage Area (Ac.)	0.82	0.82
CN	73	73
T _c (Hours)	0.06	0.05
Q _{p 10 year} (cfs)	3.1	3.1

Drainage Area 2	Pre	Post
Site Area (Ac.)	4.32	4.32
Drainage Area (Ac.)	2.22	2.22
CN	73	73
T _c (Hours)	0.28	0.28
O _n (cfs)	5.5	5.5

Stor	mwate	er Man	ageme	nt Sun	nmary	Table		
Minimum Sizing Criteria	Volume Required		Volume Required Volume Provided		Volume Provided		SWM Practice	Notes
Water Quality Volume (WQ _v) Cubic Feet	1A 713	1B 629	2 NA	1A 713	1B 629	2 NA	Site Design	Sensitive Development Credit
Recharge Volume(Re _v)	100	88	NA	100	88	NA	Site Design	Sensitive Development Credit
Channel Protection Volume (Cp _v)		N/A			N/A		N/A	One-year post development peak discharge rate < 2.0 efs
Overbank Flood Protection (Qp)	N/A		N/A		N/A	Site has a direct discharge to a tidal outfall		
Extreme Flood Volume (Q _f)		N/A			N/A	(10)	N/A	Site has a direct discharge to a tidal outfall

ANNE ARUNDEL COUNTY
MARYLAND

PRIOR PERC(S): UYES

Department of Health PERC DATA FORM

PERC	APPLICATION	No.: 102033599	

SOIL TYPE: MUCS MUGD SEWER SERVICE CATEGORY: RCA WET SEASON RESTRICTED? YES | NO HOUSE SIZE: OVE 35000

DATE TESTED: 3/3/05

PERSONS PRESENT

DURING TESTING:

TESTED IN WET SEASON? PYES

NO

SANITARIAN:

Kimberly Roy

Tones Mr. Teren and Son

TESTED IN WET SEASON? PYES

NO

DIDA

DIDA SOIL TEST RESULTS

Infollowed test at 2.5 15-1st inch Thour and 4 minutes 2rd inch Thousand 12 minutes

3600 & mound

O OTHER

SIGNIFICANT LOT LIMITATIONS

□ DRAINAGE AREA

□ PERCHED WATER ☐ STEEP SLOPES ☐ STORM DRAIN O WATER WELLS ☐ HIGH GROUNDWATER☐ POOR DRAINAGE U LIMITED AREA


COMPACTED SOILS

FILL


INCONSISTENT SOILS

LOT STAKED


Boring Rig Igreen/brown Sardy clay Monitoring pipe H20 level rose to 36 on 3/7/05 (KMR) 8 diameter 5 minute rate 13'e 9x 4.4=39.6:3=13.2e +19.0'/oss 32' total Show S-8'x32' drywells Effective area 994.7512 CHRONOLOGY



EXISTING DRAINAGE AREA



PROPOSED DRAINAGE AREA



BACKUP MOUND SYSTEM

ngineering

Bay Engineers.

Date AUGUST, 2006

Job Number

05-1562

Drawn By L.K.C.

Designed By T.L.S.

Approved By T.L.S.


Folder Reference YOUNG ERIK CHILD POINT


Scale AS SHOWN

5 OF 5 05-1562 File No.


BYWATER

101





SITE, GRADING, AND SEDIMENT CONTROL PLAN



Folder Reference YOUNG ERIK CHILD POINT

MAR 5 2007 CRITICAL AREA COM Chesapeake & Atlant

3 OF 5 05-1562